

## LIGHT SOURCE

LED quantity	3
Power max	3 W
Total lumen output (3000K)	3W: 15° - 269 lm 30° - 311 lm 60° - 202 lm Elliptical lens - 251 lm Frosted glass - 130 lm
Efficacy lm/W (3000K)	3W: 15° - 90 lm/W 30° - 104 lm/W 60° - 67 lm/W Elliptical lens - 84 lm/W Frosted glass - 43 lm/W
CRI	>80
LED Temperature	2200K - 2700K - 3000K - 4000K - RGB (available on some products only: 30° - frosted glass)
Average operational life	50.000 hours

## OPTIC

Material	PMMA
Available optics	15° - 30° - 60° - Elliptical lens - Frosted glass
Beam direction	Fixed
Flux symmetry	Symmetrical, asymmetrical

## FIXTURE

Material	Aluminum, Stainless Steel
Available finishes	Hard coat anodized: 3 - Gray 4 - Black As per material: 6 - Stainless steel AISI 316L
IP Rate	IP67
Working Temperature	-20° ÷ +40°
Integrated fixing Systems	-

## ELECTRICAL FEATURES




Driver	Remote
Dimmable	Push, 1-10V, DALI
Connection	In series at 350mA, in parallel at 24Vdc
Class	III

## MECHANICAL FEATURES


Dimensions (body)	Ø59 x 79 mm
Weight	217 gr
Installation	Wall, ceiling, floor recessed
Cut-out	Ø50 mm (recessed box A00129.30)
Use	Outdoor

## ACCESSORIES

Visors	-
Filters	-
Box/ Frame	Recessed box
Fixing system	-








A00129.30 Recessed box



A00250.40 Recessed box

## PHOTOMETRIC DATA

15° Lens – 3W	30° Lens – 3W	60° Lens – 3W	Elliptical Lens – 3W																																																																																																																
																																																																																																																			
<table> <tr> <th>H(m)</th><th>D(m)</th><th>E<sub>max</sub>(lx)</th><th>E<sub>av</sub>(lx)</th></tr> <tr> <td><b>15°</b></td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.43</td><td>1026</td><td>626</td></tr> <tr> <td><u>2.00</u></td><td>0.86</td><td>257</td><td>156</td></tr> <tr> <td><u>3.00</u></td><td>1.29</td><td>114</td><td>70</td></tr> <tr> <td><u>4.00</u></td><td>1.72</td><td>64</td><td>39</td></tr> <tr> <td><u>5.00</u></td><td>2.14</td><td>41</td><td>25</td></tr> </table>	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	<b>15°</b>				<u>1.00</u>	0.43	1026	626	<u>2.00</u>	0.86	257	156	<u>3.00</u>	1.29	114	70	<u>4.00</u>	1.72	64	39	<u>5.00</u>	2.14	41	25	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E<sub>max</sub>(lx)</th><th>E<sub>av</sub>(lx)</th></tr> <tr> <td><b>30°</b></td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.54</td><td>824</td><td>522</td></tr> <tr> <td><u>2.00</u></td><td>1.08</td><td>206</td><td>131</td></tr> <tr> <td><u>3.00</u></td><td>1.62</td><td>92</td><td>58</td></tr> <tr> <td><u>4.00</u></td><td>2.16</td><td>51</td><td>33</td></tr> <tr> <td><u>5.00</u></td><td>2.70</td><td>33</td><td>21</td></tr> </table>	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	<b>30°</b>				<u>1.00</u>	0.54	824	522	<u>2.00</u>	1.08	206	131	<u>3.00</u>	1.62	92	58	<u>4.00</u>	2.16	51	33	<u>5.00</u>	2.70	33	21	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E<sub>max</sub>(lx)</th><th>E<sub>av</sub>(lx)</th></tr> <tr> <td><b>60°</b></td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.85</td><td>320</td><td>188</td></tr> <tr> <td><u>2.00</u></td><td>1.70</td><td>80</td><td>47</td></tr> <tr> <td><u>3.00</u></td><td>2.55</td><td>36</td><td>21</td></tr> <tr> <td><u>4.00</u></td><td>3.39</td><td>20</td><td>12</td></tr> <tr> <td><u>5.00</u></td><td>4.24</td><td>13</td><td>8</td></tr> </table>	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	<b>60°</b>				<u>1.00</u>	0.85	320	188	<u>2.00</u>	1.70	80	47	<u>3.00</u>	2.55	36	21	<u>4.00</u>	3.39	20	12	<u>5.00</u>	4.24	13	8	<table> <tr> <th>H(m)</th><th>D(m)</th><th>E<sub>max</sub>(lx)</th><th>E<sub>av</sub>(lx)</th></tr> <tr> <td><b>20°x 40°</b></td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>0.45</td><td>709</td><td>428</td></tr> <tr> <td><u>2.00</u></td><td>0.90</td><td>177</td><td>107</td></tr> <tr> <td><u>3.00</u></td><td>1.36</td><td>79</td><td>48</td></tr> <tr> <td><u>4.00</u></td><td>1.81</td><td>44</td><td>27</td></tr> <tr> <td><u>5.00</u></td><td>2.26</td><td>28</td><td>17</td></tr> </table>	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	<b>20°x 40°</b>				<u>1.00</u>	0.45	709	428	<u>2.00</u>	0.90	177	107	<u>3.00</u>	1.36	79	48	<u>4.00</u>	1.81	44	27	<u>5.00</u>	2.26	28	17
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)																																																																																																																
<b>15°</b>																																																																																																																			
<u>1.00</u>	0.43	1026	626																																																																																																																
<u>2.00</u>	0.86	257	156																																																																																																																
<u>3.00</u>	1.29	114	70																																																																																																																
<u>4.00</u>	1.72	64	39																																																																																																																
<u>5.00</u>	2.14	41	25																																																																																																																
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)																																																																																																																
<b>30°</b>																																																																																																																			
<u>1.00</u>	0.54	824	522																																																																																																																
<u>2.00</u>	1.08	206	131																																																																																																																
<u>3.00</u>	1.62	92	58																																																																																																																
<u>4.00</u>	2.16	51	33																																																																																																																
<u>5.00</u>	2.70	33	21																																																																																																																
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)																																																																																																																
<b>60°</b>																																																																																																																			
<u>1.00</u>	0.85	320	188																																																																																																																
<u>2.00</u>	1.70	80	47																																																																																																																
<u>3.00</u>	2.55	36	21																																																																																																																
<u>4.00</u>	3.39	20	12																																																																																																																
<u>5.00</u>	4.24	13	8																																																																																																																
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)																																																																																																																
<b>20°x 40°</b>																																																																																																																			
<u>1.00</u>	0.45	709	428																																																																																																																
<u>2.00</u>	0.90	177	107																																																																																																																
<u>3.00</u>	1.36	79	48																																																																																																																
<u>4.00</u>	1.81	44	27																																																																																																																
<u>5.00</u>	2.26	28	17																																																																																																																
Frosted glass – 3W																																																																																																																			
																																																																																																																			
<table> <tr> <th>H(m)</th><th>D(m)</th><th>E<sub>max</sub>(lx)</th><th>E<sub>av</sub>(lx)</th></tr> <tr> <td><b>Frosted glass</b></td><td></td><td></td><td></td></tr> <tr> <td><u>1.00</u></td><td>1.11</td><td>106</td><td>58</td></tr> <tr> <td><u>2.00</u></td><td>2.22</td><td>26</td><td>15</td></tr> <tr> <td><u>3.00</u></td><td>3.33</td><td>12</td><td>6</td></tr> <tr> <td><u>4.00</u></td><td>4.44</td><td>7</td><td>4</td></tr> <tr> <td><u>5.00</u></td><td>5.55</td><td>4</td><td>2</td></tr> </table>	H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)	<b>Frosted glass</b>				<u>1.00</u>	1.11	106	58	<u>2.00</u>	2.22	26	15	<u>3.00</u>	3.33	12	6	<u>4.00</u>	4.44	7	4	<u>5.00</u>	5.55	4	2																																																																																							
H(m)	D(m)	E <sub>max</sub> (lx)	E <sub>av</sub> (lx)																																																																																																																
<b>Frosted glass</b>																																																																																																																			
<u>1.00</u>	1.11	106	58																																																																																																																
<u>2.00</u>	2.22	26	15																																																																																																																
<u>3.00</u>	3.33	12	6																																																																																																																
<u>4.00</u>	4.44	7	4																																																																																																																
<u>5.00</u>	5.55	4	2																																																																																																																

## NOTES

Provided with 100 cm neoprene cable.