

Downlights




IP40


500


360 g


Ø54


2


SD CM


TM 66


IC


UL LISTED

Ø54
[2 1/8"]

135
[5 3/8"]

Ø60
[2 3/8"]

Ø40
[1 5/8"]

Ariel Am fixing frame

FIXING FRAME	A01539._0
--------------	-----------


FRAME FINISH
_ See module finish

Ariel Am module

500mA Lumen Output 3000K	9W 500mA - 900 lm
14° Lens [1]	7Q4408._ _ _ _ -UL
18° Lens	784408._ _ _ _ -UL
24° Lens	7G4408._ _ _ _ -UL
33° Lens	7E4408._ _ _ _ -UL
52° Lens	754408._ _ _ _ -UL

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
● 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		

[1] 14° Lens not interchangeable



SUGGESTED DRIVERS (not included)

500mA CC36-R-500-NF p. 245

INTERCHANGEABLE ACCESSORIES



p. 234

EXAMPLE CODE COMPOSITION

123456.	-UL
	OPTICAL FILTER
	DECORATIVE RING
	CCT
	MODULE FINISH