


Ariel Am IP55

Downlights | IP55 | Class III | Dimmable



LIGHT SOURCE & OPTIC

Power

9W
13W

Lens

14° - not interchangeable
18° / 24° / 33° / 52° - interchangeable

Beam Direction

Fixed, Symmetrical

Material

PMMA

LED quantity

1

Binning

2 MacAdam steps

Color temperature & quality

2200K CRI>90
2400K CRI>90
2700K CRI>90/95
3000K CRI>80/90/95
3500K CRI>90/95
4000K CRI>90

Lifetime

(L70) >77.000 hrs

FIXTURE

Dimensions

Ø 60mm x Hmax 109mm

Material

Aluminium

Body finishes

Warm White (RAL 9010)
White (RAL 9003)
Gray White (RAL 9002)
Gothic Cement (RAL 7033)
Gray (RAL 7012)
Beige Gray (RAL 7006)
Brown (RAL 8019)
Black (RAL 9005)

Decorative ring finishes

Gold Chrome
Shiny Chrome
Satin Gold
Satin Nickel
Black

Weight

250gr

Mounting

Recessed: cut out Ø 54mm

Fixing

Fixing frame with springs

Working temperature

-20° / +40°

ELECTRICAL FEATURES

Power supply

Constant current:
500 mA
700mA
Typical Vf= 18V

Driver requirement

Remote (not included)


Control

On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI

Ariel Am IP55

PHOTOMETRIC DATA (3000K CRI>90)

9W - 18° | UGR 13




| H (m) | D (m) | Eav (lx) |
|----------|----------|-------------|
| 1 | 0.32 | 3087 |
| 2 | 0.64 | 772 |
| 3 | 0.96 | 343 |
| 4 | 1.28 | 193 |
| 5 | 1.60 | 123 |

Total lumen output
712 lm

Efficacy
79 lm/W

9W - 24° | UGR 15




| H (m) | D (m) | Eav (lx) |
|----------|----------|-------------|
| 1 | 0.41 | 1919 |
| 2 | 0.83 | 480 |
| 3 | 1.24 | 213 |
| 4 | 1.66 | 120 |
| 5 | 2.07 | 77 |

Total lumen output
685 lm

Efficacy
76 lm/W

9W - 33° | UGR 17




| H (m) | D (m) | Eav (lx) |
|----------|----------|-------------|
| 1 | 0.60 | 980 |
| 2 | 1.21 | 245 |
| 3 | 1.81 | 109 |
| 4 | 2.41 | 61 |
| 5 | 3.02 | 39 |

Total lumen output
618 lm

Efficacy
69 lm/W

9W - 52° | UGR 21




| H (m) | D (m) | Eav (lx) |
|----------|----------|-------------|
| 1 | 0.97 | 550 |
| 2 | 1.94 | 138 |
| 3 | 2.91 | 61 |
| 4 | 3.88 | 34 |
| 5 | 4.85 | 22 |

Total lumen output
682 lm

Efficacy
76 lm/W

9W - 14° | UGR 10



| H (m) | D (m) | Eav (lx) |
|----------|----------|-------------|
| 1 | 0.25 | 4298 |
| 2 | 0.50 | 1074 |
| 3 | 0.76 | 478 |
| 4 | 1.01 | 269 |
| 5 | 1.26 | 172 |


Total lumen output
659 lm

Efficacy
73 lm/W

Ariel Am IP55

PHOTOMETRIC DATA (3000K CRI>90)

13W - 18° | UGR 13




| H (m) | D (m) | Eav (lx) |
|----------|----------|-------------|
| 1 | 0.32 | 3890 |
| 2 | 0.65 | 972 |
| 3 | 0.97 | 432 |
| 4 | 1.30 | 243 |
| 5 | 1.62 | 156 |

Total lumen output
937 lm

Efficacy
72 lm/W

13W - 24° | UGR 15




| H (m) | D (m) | Eav (lx) |
|----------|----------|-------------|
| 1 | 0.42 | 2406 |
| 2 | 0.64 | 602 |
| 3 | 1.25 | 267 |
| 4 | 1.67 | 150 |
| 5 | 2.09 | 96 |

Total lumen output
883 lm

Efficacy
68 lm/W

13W - 33° | UGR 17




| H (m) | D (m) | Eav (lx) |
|----------|----------|-------------|
| 1 | 0.60 | 1228 |
| 2 | 1.21 | 307 |
| 3 | 1.81 | 136 |
| 4 | 2.41 | 77 |
| 5 | 3.02 | 49 |

Total lumen output
780 lm

Efficacy
60 lm/W

13W - 52° | UGR 21




| H (m) | D (m) | Eav (lx) |
|----------|----------|-------------|
| 1 | 0.97 | 680 |
| 2 | 1.94 | 170 |
| 3 | 2.91 | 76 |
| 4 | 3.68 | 43 |
| 5 | 4.85 | 27 |

Total lumen output
844 lm

Efficacy
65 lm/W

13W - 14° | UGR 10



| H (m) | D (m) | Eav (lx) |
|----------|----------|-------------|
| 1 | 0.25 | 5271 |
| 2 | 0.51 | 1318 |
| 3 | 0.76 | 586 |
| 4 | 1.02 | 329 |
| 5 | 1.27 | 211 |

Total lumen output
863 lm

Efficacy
66 lm/W

Ariel Am IP55

INTERCHANGEABLE ACCESSORIES

Optical Filters

Hex louver
Elliptical Filter
Prismatic filter
Softening lens

Lenses

18° / 24° / 33° / 52°

Filter holder rings

Black
Gold Chrome
Satin Gold
Satin Nickel
Shiny Chrome

INSTALLATION ACCESSORIES


Fixing rame (A01341._0)

Necessary element: please specify always 1 frame for each Fixture in the purchase order

SUGGESTED REMOTE DRIVERS


On/Off :

CC10-F-500-SI



Ø 28


CC23-F-700-SP



Ø 37


Multifunction (DALI 2, 0/1-10V, PUSH RIPPLE FREE, AM DIMMING):

CC15-D-500-S



Ø 30

CC15-D-700-S



Ø 30

Other options upon request