

Ariel In&Out F

Downlights



IP40

500
600

530 g

Ø64

2

SD
CM

2,5

TM
66

Ariel In&Out F fixing frame

FIXING FRAME A01850_0

FRAME FINISH

- 4 Black
- 3 Gray

Ariel In&Out F module

500 / 600mA Lumen Output 3000K	9W 500mA - 900 lm	11W 600mA - 1100 lm
14° Lens [1]	7Q4421.____	7Q4993.____
18° Lens	784421.____	784993.____
24° Lens	7G4421.____	7G4993.____
33° Lens	7E4421.____	7E4993.____
52° Lens	754421.____	754993.____

MODULE FINISH

- 4 Black
- M8 Brown
- G3 Gray
- C Gothic Cement
- G7 Beige Gray
- A6 Gray White
- S Warm White
- 7 White

CCT


- U1 2200K CRI > 90
- B2 2400K CRI > 90
- X 2700K CRI > 90
- X1 2700K CRI > 95
- 6 3000K
- W 3000K CRI > 90
- W1 3000K CRI > 95
- K 3500K CRI > 90
- K1 3500K CRI > 95
- D 4000K CRI > 90

DECORATIVE RING

- 4 Black
- I Gold Chrome
- 8 Satin Gold
- N Satin Nickel
- 1 Shiny Chrome

OPTICAL FILTER

- W Without Filter
- E Elliptical Filter
- H Hex Louver
- P Prismatic Filter
- S Softening Lens




[1] 14° Lens not interchangeable

FIXING FRAME



MODULE



discover more

SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
600mA	CC20-F-600-NI	p. 701

INTERCHANGEABLE ACCESSORIES



p. 676



Hole saw
A00830.H0

EXAMPLE CODE COMPOSITION

