

Ariel In&Out m Plug&Play



Downlights

● Plug&Play System



IP40

500
600

540 g

Ø67 P&P

2

2,6



Ariel In&Out m Plug&Play fixing frame

FIXING FRAME		FRAME FINISH
A01853._0		_ See module finish

Ariel In&Out m Plug&Play module

500 / 600mA Lumen Output 3000K	9W 500mA - 900 lm	11W 600mA - 1100 lm
14° Lens	7Q4625._ _ _ _	7Q4626._ _ _ _
18° Lens	784625._ _ _ _	784626._ _ _ _
24° Lens	7G4625._ _ _ _	7G4626._ _ _ _
33° Lens	7E4625._ _ _ _	7E4626._ _ _ _
52° Lens	754625._ _ _ _	754626._ _ _ _

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● 4 Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
● 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		



SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
600mA	CC20-F-600-NI	p. 701

INTERCHANGEABLE ACCESSORIES



p. 676

EXAMPLE CODE COMPOSITION

