

# Ariel In&Out m Wall Washer

Downlights | IP40 | Class III | Dimmable




Fixing  
frame



+

Module



## LIGHT SOURCE & OPTIC

### Power

9W  
13W

### Lens

Wall washer

### Beam Direction

Adjustable:  
Tilting +/-90°, rotating +/-355°,  
Asymmetrical

### Material

PMMA

### LED quantity

1

### Binning

2 MacAdam steps

### Color temperature & quality

2200K CRI>90  
2400K CRI>90  
2700K CRI>90/95  
3000K CRI>80/90/95  
3500K CRI>90/95  
4000K CRI>90

### Lifetime

(L70) >77.000 hrs

## FIXTURE

### Dimensions

Ø 74mm x Hmax 124mm

### Material

Aluminium

### Body finishes

Warm White (RAL 9010)  
White (RAL 9003)  
Gray White (RAL 9002)  
Gothic Cement (RAL 7033)  
Gray (RAL 7012)  
Beige Gray (RAL 7006)  
Brown (RAL 8019)  
Black (RAL 9005)

### Weight

540gr

### Mounting

Recessed: cut out Ø 67mm

### Fixing

Fixing frame with springs

### Working temperature

-20° / +40°

## ELECTRICAL FEATURES

### Power supply

Constant current:  
500 mA  
700mA  
Typical Vf= 18V

### Driver requirement

Remote (not included)

### Control


On/off  
Push switch  
Phase Cut  
0/1-10 V  
Casambi  
DALI

# Ariel In&Out m Wall Washer


PHOTOMETRIC DATA (3000K CRI>90)

9W - WW | UGR 33

13W - WW | UGR 34



H (m)	D (m)	Eav (lx)
1	1.55	188
2	3.10	47
3	4.64	21
4	6.19	12
5	7.74	8



H (m)	D (m)	Eav (lx)
1	1.55	243
2	3.10	61
3	4.65	27
4	6.20	15
5	7.75	10

Total lumen output  
753 lm

Efficacy  
84 lm/W

Total lumen output  
975 lm

Efficacy  
75 lm/W

# Ariel In&Out m Wall Washer


## INSTALLATION ACCESSORIES


Fixing rame (A01293.\_0)  
Necessary element: please specify always 1  
frame for each Fixture in the purchase order

## SUGGESTED REMOTE DRIVERS


### On/Off :

CC10-F-500-SI



 Ø 28


CC23-F-700-SP



 Ø 37


### Multifunction (DALI 2, 0/1-10V, PUSH RIPPLE FREE, AM DIMMING):

CC15-D-500-S



 Ø 30

CC15-D-700-S



 Ø 30

Other options upon request