

Downlights



IP55

500
700

480 g


Ø86

2

2,5

Ariel mR IP55 fixing frame

FIXING FRAME	A01270._0
--------------	-----------



FRAME FINISH
_ See module finish

Ariel mR IP55 module

[1] 14° Lens not interchangeable

FIXING FRAME



MODULE



500 / 700mA Lumen Output 3000K	9W 500mA - 880 lm	13W 700mA - 1080 lm
14° Lens [1]	7Q4526._ _ _ _	7Q4527._ _ _ _
18° Lens	784526._ _ _ _	784527._ _ _ _
24° Lens	7G4526._ _ _ _	7G4527._ _ _ _
33° Lens	7E4526._ _ _ _	7E4527._ _ _ _
52° Lens	754526._ _ _ _	754527._ _ _ _

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
○ 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		



discover more

SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
700mA	CC20-F-700-N	p. 702

INTERCHANGEABLE ACCESSORIES



p. 676

EXAMPLE CODE COMPOSITION

123456.	OPTICAL FILTER
	DECORATIVE RING
	CCT
	MODULE FINISH