

Continuum i IP67 Louver

DGA

Linear with Lenses



discover more




Continuum i IP67 Louver



Linear with Lenses



IP67	WIPS	24V	IK 10	1 m	890 g 1660 g 2440 g 3210 g 3980 g



Lumen Output 3000K
30W/m - 10° Lens: 2500 lm/m


FINISH	CCT
● 4 Black	● U 2200K
	● Y 2700K
	● W 3000K CRI > 90
	● 6 3000K
	● 9 4000K
	● 8 TUNABLE WHITE

Continuum i IP67 Louver

24V	9W	18W	27W	36W
Length	30 cm	60 cm	90 cm	120 cm
10° Lens	734462._ _	734463._ _	734464._ _	734465._ _
25° Lens	764462._ _	764463._ _	764464._ _	764465._ _
40° Lens	744462._ _	744463._ _	744464._ _	744465._ _
60° Lens	754462._ _	754463._ _	754464._ _	754465._ _
Elliptical Lens	774462._ _	774463._ _	774464._ _	774465._ _



IP67	WIPS	230V	IK 10	1 m	1260 g 2200 g 3040 g 3870 g 4700 g



Lumen Output 3000K
30W/m - 10° Lens: 2500 lm/m

FINISH	CCT
● 4 Black	● U 2200K
	● Y 2700K
	● W 3000K CRI > 90
	● 6 3000K
	● 9 4000K

Continuum i IP67 Louver 230V

220-240Vac	11W	21W	30W	40W
Length	30 cm	60 cm	90 cm	120 cm
10° Lens	734466._ _	734467._ _	734468._ _	734469._ _
25° Lens	764466._ _	764467._ _	764468._ _	764469._ _
40° Lens	744466._ _	744467._ _	744468._ _	744469._ _
60° Lens	754466._ _	754467._ _	754468._ _	754469._ _
Elliptical Lens	774466._ _	774467._ _	774468._ _	774469._ _

Continuum i IP67 louver 230V DALI

220-240Vac	11W	21W	30W	40W
Length	30 cm	60 cm	90 cm	120 cm
10° Lens	734470._ _	734471._ _	734472._ _	734473._ _
25° Lens	764470._ _	764471._ _	764472._ _	764473._ _
40° Lens	744470._ _	744471._ _	744472._ _	744473._ _
60° Lens	754470._ _	754471._ _	754472._ _	754473._ _
Elliptical Lens	774470._ _	774471._ _	774472._ _	774473._ _

SUGGESTED DRIVERS (not included)

24Vdc CV70-F-24-N p. 292
24Vdc TW CV100-L-24-NL p. 291

ACCESSORIES

Recessed box L 30 cm in Stainless Steel AISI 316L	Recessed box L 60 cm in Stainless Steel AISI 316L	Recessed box L 90 cm in Stainless Steel AISI 316L	Recessed box L 120 cm in Stainless Steel AISI 316L	Watertight connector 24Vdc	Watertight connector 220-240Vac
A01209.60	A01210.60	A01211.60	A01212.60	A00357.40	A01023.40
Recessed box for Continuum i IP67 Louver 24V	Recessed box for Continuum i IP67 Louver 230V				
A01213.60	A01214.60	A01215.60	A01216.60		