
























GEMMA 40 N

-  IP40
-  Class III
-  Montaggio a soffitto
Ceiling mounting
-  Versione RGB con cavo in neoprene 100 cm
RGB version with 100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in serie 350mA o 500mA
Connect in series at 350mA or 500mA
-  115 gr
-  Altamente riciclabile
Highly recyclable



GEMMA 40 N

	1W 350mA	2W 500mA	3W 350mA	3W RGB 350mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	100lm	150lm	300lm	350lm		
 10° Lens	734259._ _	734260._ _			<ul style="list-style-type: none">  1 Cromo Lucido Shiny Chrome  3 Grigio - Gray  4 Nero - Black  7 Bianco - White  W All White  U 2200K  Y 2700K  6 3000K  W 3000K CRI > 90  9 4000K  7 RGB <p><small>Available on some products only</small></p>	
 30° Lens	764259._ _	764260._ _		764354._ 7		
 60° Lens	754259._ _	754260._ _	754353._ _			
 Vetro trasparente Transparent glass	724259._ _	724260._ _	724353._ _			
 Vetro satinato Frosted glass	714259._ _	714260._ _	714353._ _	714354._ 7		



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA CC20-F-350-N
500mA CC20-F-500-N
350mA RGB CC36-X-350-N

EXAMPLE CODE COMPOSITION
123456.

