

Micro IP68



IP68 Projectors



IP68

WIPS


350

12V

5 m

370 g

2



	350mA	3W
Lumen Output 3000K		350mA - 270 lm
15° Lens	7A4033.6 _	
30° Lens	764033.6 _	
60° Lens	754033.6 _	
Frosted Glass	714033.6 _	
Elliptical Lens	774033.6 _	

FINISH

6 Stainless Steel
AISI 316L

CCT

U 2200K
Y 2700K
6 3000K
W 3000K CRI > 90
9 4000K
1 5000K

	12V	4W
Lumen Output 3000K		12Vdc - 270 lm
15° Lens	7A4766.6 _	
30° Lens	764766.6 _	
60° Lens	754766.6 _	
Frosted Glass	714766.6 _	
Elliptical Lens	774766.6 _	



SUGGESTED DRIVERS (not included)

350mA	CC14-F-350-PI	p. 704
12Vdc	CV30-F-12-PI	p. 706

ACCESSORIES

35
Ø39
9
Low glare visor
Stainless Steel 316L
A00846.60

Ø39
35
Stainless steel stake
A00847.60

Ø30
152
Waterlight connector
A00277.60

37
22 / 36,5
Waterlight connector
A00387.40

EXAMPLE CODE COMPOSITION

123456.	CCT	FINISH
---------	-----	--------