

Downlights



IP40

400

680 g

Ø67


[2 5/8"]

SD CM

TM 66

IC

UL LISTED




Saturno Am fixing frame

FRAME FINISH	
FIXING FRAME	A01548._0
_ See module finish	

Saturno Am module

[1] 12° Lens not interchangeable



400mA Lumen Output 3000K	14W 400mA - 1550 lm
12° Lens [1]	7Q4602._ _ _ _ -UL
18° Lens	784602._ _ _ _ -UL
24° Lens	7G4602._ _ _ _ -UL
33° Lens	7E4602._ _ _ _ -UL
52° Lens	754602._ _ _ _ -UL

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
● 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		



SUGGESTED DRIVERS (not included)

400mA CC36-R-400-NF p. 244

INTERCHANGEABLE ACCESSORIES



p. 235

EXAMPLE CODE COMPOSITION

