

Saturno In&Out F



Downlights



- IP40
- 500
- 830 g
- Ø86
- 2
- SD CM
- TM 86
- 2,5

Saturno In&Out F fixing frame

FIXING FRAME A01854._0

- FRAME FINISH
- 4


 Black
- 3

 Gray

Saturno In&Out F module

500mA Lumen Output 3000K	18W 500mA - 2100 lm
12° Lens [1]	7Q4416.____
18° Lens	784416.____
24° Lens	7G4416.____
33° Lens	7E4416.____
52° Lens	754416.____

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
● 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		



[1] 12° Lens not interchangeable

FIXING FRAME

MODULE



SUGGESTED DRIVERS (not included)

500mA CC20-F-500-N p. 700

INTERCHANGEABLE ACCESSORIES



EXAMPLE CODE COMPOSITION

123456.____
|
| OPTICAL FILTER
| DECORATIVE RING
| CCT
| MODULE FINISH