

Downlights



IP40


500

830 g

Ø102

2

2,5



Saturno mR fixing frame

FRAME FINISH	
FIXING FRAME	A01269._0
_ See module finish	

Saturno mR module

[1] 12° Lens not interchangeable



500mA Lumen Output 3000K	18W 500mA - 2100 lm
12° Lens [1]	7Q4457._ _ _ _
18° Lens	784457._ _ _ _
24° Lens	7G4457._ _ _ _
33° Lens	7E4457._ _ _ _
52° Lens	754457._ _ _ _

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
○ 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		

discover more

SUGGESTED DRIVERS (not included)

INTERCHANGEABLE ACCESSORIES

EXAMPLE CODE COMPOSITION

500mA CC20-F-500-N p. 700



p. 677

123456.

OPTICAL FILTER

DECORATIVE RING

CCT

MODULE FINISH