

Downlights

● Plug&Play System



IP40

400

1420 g

Ø104
[4 1/8"]

P&P


TM 66

IC

C-UL-US
LISTED

Saturno RF Plug&Play fixing frame

FIXING FRAME	A01770.40
--------------	-----------



Saturno RF Plug&Play module

400mA Lumen Output 3000K	14W 400mA - 1550 lm
12° Lens	7Q4935.____-UL
18° Lens	784935.____-UL
24° Lens	7G4935.____-UL
33° Lens	7E4935.____-UL
52° Lens	754935.____-UL

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
● 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		

FIXING FRAME

MODULE



SUGGESTED DRIVERS (not included)

400mA CC36-R-400-NF p. 244

INTERCHANGEABLE ACCESSORIES



Hole saw
A01258.H0

EXAMPLE CODE COMPOSITION

123456. -UL
OPTICAL FILTER
DECORATIVE RING
CCT
MODULE FINISH