

Spillo L

Bollards | IP67 | Class III | Dimmable



Ø20

LIGHT SOURCE & OPTIC

Power

1W

2W

Emission

Diffused

Beam Direction

Fixed, Symmetrical

Material

PMMA

LED quantity

1

Binning

2 MacAdam steps

Color temperature & quality

2700K CRI>80

2700K CRI>90

3000K CRI>90

4000K CRI>90

Lifetime

(L90) >60.000 hrs

FIXTURE

Dimensions

Ø 8mm x L 250-400-550mm

Material

Aluminium

Body finishes

Black

Dark bronze

Gray

Weight

90-95-100gr

Mounting

On floor

Fixing

Stake

Working temperature

-20° / +40°

ELECTRICAL FEATURES

Power supply

Constant current:

350 mA

500 mA

Typical Vf= 3V

Driver requirement

Remote (not included)

Control

On/off

Push switch

Phase Cut

0/1-10 V

Casambi


DALI

Feature

Water Infiltration Protection System

PHOTOMETRIC DATA (3000K CRI>90)


1W - diffuse | UGR 35



Total lumen output
36 lm

Efficacy
18 lm/W

2W - diffuse | UGR 36




Total lumen output
48 lm

Efficacy
24 lm/W

INSTALLATION ACCESSORIES


Watertight connector (A00357.40)



SUGGESTED REMOTE DRIVERS

On/Off :


CC14-F-350/500-PI



Ø 44


Multifunction (DALI 2, 0/1-10V, PUSH RIPPLE FREE, AM DIMMING):

CC20-D-350-P



Ø 60

CV25-D-500-P



Ø 60

Other options upon request