

TONO iR IP67



IP67



Class III



Incasso a parete, pavimento
Wall, floor recessed



WIPS - Water Infiltration Protection System



Carrabile 2000 kg
Drive over up to 2000 kg



Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)



Collegare in serie 500mA o 900mA
Connect in series at 500mA or 900mA



780 gr



Altamente riciclabile
Highly recyclable




Ottica arretrata
Facile da orientare
Adatto a molteplici
applicazioni

Backward optics
Easy to adjust
Suitable for multiple
applications

■ TONO iR IP67

	3W 900mA	6W 500mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	200lm	450lm		
3° Lens	7T3684._ _		3 Grigio - Gray	Y 2700K
10° Lens	733683._ _		4 Nero - Black	W 3000K CRI > 90
30° Lens	763683._ _		6 Acciaio Inox Stainless Steel AISI 316L	6 3000K
50° Lens	7D3683._ _			J 3500K
				9 4000K



■ TONO iR IP67

CON NIDO D'APE - WITH HEX LOUVER

	3W 900mA	6W 500mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	200lm	450lm		
3° Lens	7T3686._ _		3 Grigio - Gray	Y 2700K
10° Lens	733685._ _		4 Nero - Black	W 3000K CRI > 90
30° Lens	763685._ _		6 Acciaio Inox Stainless Steel AISI 316L	6 3000K
50° Lens	7D3685._ _			J 3500K
				9 4000K

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

500mA CC20-F-500-N
900mA CC20-F-900-N

ACCESSORI
ACCESSORIES



Controcassa materiale plastico
Recessed box in plastic
A00276.40



Controcassa in alluminio
Recessed box in aluminum
A00204.30



Connettore stagno
Watertight connector
A00387.40



Ø 92 mm

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH