
Tono RF

Indoor | Downlights | IP40 | Class III | Dimmable





LIGHT SOURCE & OPTIC

Power
3W
6W /9W

Lens
3° - 3W
10°/ 30°/ 50° - 6/9W

Beam Direction
Adjustable (Symmetrical):
Tilting +/- 25°, rotating +/- 360°,

Material
PMMA

LED quantity
1

Binning
2 MacAdam steps

Color temperature & quality
2200K CRI>80
2700K CRI>80
3000K CRI>80/90
3500K CRI>80
4000K CRI>80

Lifetime (Ta 25°)
L_{90} >60.500 hrs

Output (3000K CRI>90)
265 lm @ 900mA
578 lm @ 500mA / 784 lm @ 700mA

FIXTURE

Dimensions
Ø 120mm x H 85mm (76mm - 3/6W)

Material
Aluminium

Body finishes
White (RAL 9003)
Oyster white (RAL 1013)
Gothic Cement (RAL 7033)
Black (RAL 9005)
Gold
Corten

Weight
320gr

Mounting
Recessed: cut out Ø 86mm

Fixing
Fixing Frame

Working temperature
-20° / +40°

ELECTRICAL FEATURES

Power supply
Constant current:
900mA
500mA / 700mA
Typical Vf= 3V (3W)
Typical Vf= 12V (6/9 W)

Driver requirement
Remote (not included)


Control
On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI

Product specifications and data are subject to change without warning, due to continue technical upgrades. Images are indicative of the quality and style of the product, but may not represent the precise details of the item you receive. Since we are constantly working to make improvements and for aesthetic reasons, cables and/or electrical elements are often not shown or specified.
For further information please check our website www.dga.it or send us an e-mail to ufficiotecnico@dga.it | Vs 021126

Tono RF

PHOTOMETRIC DATA (3000K CRI>80)

3W - 3° | UGR 7




H (m)	D (m)	Eav (lx)
1	0.11	3323
2	0.22	831
3	0.33	369
4	0.45	208
5	0.56	133

Total lumen output
219 lm

Efficacy
73 lm/W

6W - 10° | UGR 9




H (m)	D (m)	Eav (lx)
1	0.27	3438
2	0.55	859
3	0.82	382
4	1.10	215
5	1.37	138

Total lumen output
520 lm

Efficacy
87 lm/W

6W - 30° | UGR 13




H (m)	D (m)	Eav (lx)
1	0.45	1283
2	0.90	321
3	1.35	143
4	1.80	80
5	2.25	51

Total lumen output
466 lm

Efficacy
78 lm/W

6W - 50° | UGR 15




H (m)	D (m)	Eav (lx)
1	0.69	653
2	1.37	163
3	2.06	73
4	2.74	41
5	3.43	26

Total lumen output
442 lm

Efficacy
74 lm/W

9W - 10° | UGR 10




H (m)	D (m)	Eav (lx)
1	0.28	4495
2	0.56	1124
3	0.84	499
4	1.12	281
5	1.40	180

Total lumen output
703 lm

Efficacy
78 lm/W

9W - 30° | UGR 14




H (m)	D (m)	Eav (lx)
1	0.49	1600
2	0.98	400
3	1.47	178
4	1.96	100
5	2.45	64

Total lumen output
640 lm

Efficacy
71 lm/W

9W - 50° | UGR 20



H (m)	D (m)	Eav (lx)
1	0.70	857
2	1.40	214
3	2.11	95
4	2.81	54
5	3.51	34

Total lumen output
599 lm


Efficacy
66 lm/W

Product specifications and data are subject to change without warning, due to continue technical upgrades. Images are indicative of the quality and style of the product, but may not represent the precise details of the item you receive. Since we are constantly working to make improvements and for aesthetic reasons, cables and/or electrical elements are often not shown or specified.
For further information please check our website www.dga.it or send us an e-mail to ufficiotecnico@dga.it | Vs 021126

Tono RF

PHOTOMETRIC DATA (3000K CRI>80) - with hex louver

3W - 3° | UGR 1




H (m)	D (m)	Eav (lx)
1	0.10	3157
2	0.21	789
3	0.31	351
4	0.41	197
5	0.52	126

Total lumen output
166 lm

Efficacy
55 lm/W

6W - 10° | UGR 3




H (m)	D (m)	Eav (lx)
1	0.25	3181
2	0.51	795
3	0.76	353
4	1.01	215
5	1.27	138

Total lumen output
413 lm

Efficacy
69 lm/W

6W - 30° | UGR 8




H (m)	D (m)	Eav (lx)
1	0.41	1111
2	0.82	278
3	1.23	123
4	1.64	69
5	2.05	44

Total lumen output
346 lm

Efficacy
58 lm/W

6W - 50° | UGR 8




H (m)	D (m)	Eav (lx)
1	0.59	579
2	1.18	145
3	1.76	64
4	2.35	36
5	2.94	23

Total lumen output
297 lm

Efficacy
50 lm/W

9W - 10° | UGR 14




H (m)	D (m)	Eav (lx)
1	0.25	4108
2	0.51	1027
3	0.76	456
4	1.02	257
5	1.27	164

Total lumen output
536 lm

Efficacy
59 lm/W

9W - 30° | UGR 4




H (m)	D (m)	Eav (lx)
1	0.41	1438
2	0.82	359
3	1.24	160
4	1.65	90
5	2.06	57

Total lumen output
447 lm

Efficacy
50 lm/W

9W - 50° | UGR 20



H (m)	D (m)	Eav (lx)
1	0.59	757
2	1.18	189
3	1.77	84
4	2.36	47
5	2.95	30

Total lumen output
389 lm


Efficacy
43 lm/W

Product specifications and data are subject to change without warning, due to continue technical upgrades. Images are indicative of the quality and style of the product, but may not represent the precise details of the item you receive. Since we are constantly working to make improvements and for aesthetic reasons, cables and/or electrical elements are often not shown or specified.
For further information please check our website www.dga.it or send us an e-mail to ufficiotecnico@dga.it | Vs 021126

Tono RF


INSTALLATION ACCESSORIES

Fixing rame (A00656.30)
Necessary element: please specify always 1 frame for each Fixture in the purchase order



INSTALLATION TOOL

Hole saw (A00833.H0)
available for easier installation



SUGGESTED REMOTE DRIVERS

On/Off :
CC20-F-500-N




CC20-F-700-N




CC20-F-900-N




Multifunction (DALI 2, 0/1-10V, PUSH RIPPLE FREE, AM DIMMING):
CC15-D-500-S



CC15-D-700-S



CC25-DM-900-N



Other options upon request

Product specifications and data are subject to change without warning, due to continue technical upgrades. Images are indicative of the quality and style of the product, but may not represent the precise details of the item you receive. Since we are constantly working to make improvements and for aesthetic reasons, cables and/or electrical elements are often not shown or specified.
For further information please check our website www.dga.it or send us an e-mail to ufficiotecnico@dga.it | Vs 021126