


Arco 50 iL

Step Lights | IP67 | Class III | Dimmable



LIGHT SOURCE & OPTIC

Power

1W
2W

Optics

Single light emission
Double light emission
Triple light emission

Beam Direction

Fixed

Material

PMMA

LED quantity

1

Binning

2 MacAdam steps

Color temperature & quality

2200K CRI>80
2700K CRI>80
3000K CRI>80
4000K CRI>80

Lifetime

(L85) >66.000 hrs

FIXTURE

Dimensions

Ø 50mm x H 94mm

Material

Aluminium

Body finishes

Black
Titanium
Gray
Stainless Steel AISI316L

Weight

250gr

Mounting

Semi-recessed

Fixing

Floor Recessed:
Aluminum recessed box
Plastic recessed box

Working temperature

-20° / +40°

ELECTRICAL FEATURES

Power supply

Constant current:
350 mA (1W)
500 mA (2W)
Typical Vf= 3V
Constant tension:
24Vdc (1/2W)

Driver requirement

Remote (not included)

Control

On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI

Feature

Water Infiltration Protection System

1W - SL | UGR 0



Efficacy
8 lm/W

BUG rating
B0 U1 G0

2W - SL | UGR 0




Efficacy
6 lm/W

BUG rating
B0 U1 G0


Arco 50 iL

INSTALLATION ACCESSORIES


Alluminium recessed box (A00129.30)



Plastic recessed box (A00250.40)




Watertight connector (A00387.40)




SUGGESTED REMOTE DRIVER


On/off:
CC14-F-350/500-PI




CV30-F-24-PI



Multifunction (DALI 2, 0/1-10V, PUSH):
CC20-D-350/500-P



Dimmable (DALI 2):
CV25-D-24-PI



Other options upon request