



IP68 Recessed



[1] 6W use only in permanent immersion

350 / 500 / 700mA	3W	6W [1]	3W RGBW
Lumen Output 3000K	350mA - 310 lm	500mA - 450 lm	700mA - 155 lm
15° Lens	7A4324.6 _	7A4327.6 _	
30° Lens	764324.6 _	764327.6 _	764929.67
60° Lens	754324.6 _	754327.6 _	
Frosted Glass	714324.6 _	714327.6 _	714929.67
Elliptical Lens	774324.6 _	774327.6 _	

FINISH

6 Stainless Steel
AISI 316L

CCT

- U 2200K
 - Y 2700K
 - 6 3000K
 - 9 4000K
 - 1 5000K
 - 7 RGBW
- RGBW available on some products only





12V	3W	6W [1]
Lumen Output 3000K	12Vdc - 310 lm	12Vdc - 450 lm
15° Lens	7A4325.6 _	7A4328.6 _
30° Lens	764325.6 _	764328.6 _
60° Lens	754325.6 _	754328.6 _
Frosted Glass	714325.6 _	714328.6 _
Elliptical Lens	774325.6 _	774328.6 _



SUGGESTED DRIVERS (not included)

350mA	CC14-F-350-PI	p. 704
500mA	CC14-F-500-PI	p. 704
RGBW	CC50-X-700-NL	p. 702
12Vdc	CV20-F-12-PI	p. 706

ACCESSORIES



EXAMPLE CODE COMPOSITION

123456 CCT FINISH