

Aria 1

Indoor | Projectors | IP40 | Class III | Dimmable







LIGHT SOURCE & OPTIC

Power
1W
2W

Lens
20°/30°/50°

Beam Direction
Adjustable: +/- 120°, rotating +/- 355°
Symmetrical

Material
PMMA

LED quantity
1

Binning
2 MacAdam steps

Color temperature & quality
2200K CRI>80
2700K CRI>90
3000K CRI>90
3500K CRI>90
4000K CRI>90

Lifetime (Ta 25°)
L_{85} >55.000 hrs

Source flux (3000K CRI>90)
86 lm @ 350mA / 111 lm @ 500mA

FIXTURE

Dimensions
Ø 9mm x H 24mm (cylinder)

Material
Aluminium

Body finishes
Black (RAL 9005)
Gold Chrome
Grey (RAL 7012)
Shiny Chrome
Champagne gold

Weight
60gr

Mounting
On surface

Fixing
Ring Nut

Working temperature
-20° / +40°

ELECTRICAL FEATURES

Power supply
Constant Current:
350 mA
500 mA
Typical Vf=3V

Driver requirement
Remote (not included)


Control
On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI

Product specifications and data are subject to change without warning, due to continue technical upgrades. Images are indicative of the quality and style of the product, but may not represent the precise details of the item you receive. Since we are constantly working to make improvements and for aesthetic reasons, cables and/or electrical elements are often not shown or specified.
For further information please check our website www.dga.it or send us an e-mail to ufficiotecnico@dga.it | Vs 221026

Aria 1

PHOTOMETRIC DATA (3000K CRI>90)

1W - 20° | UGR 23




H (m)	D (m)	Eav (lx)
1	0.44	107
2	0.88	27
3	1.32	12
4	1.77	7
5	2.21	4

Total lumen output
51 lm

Efficacy
52 lm/W

1W - 30° | UGR 25




H (m)	D (m)	Eav (lx)
1	0.52	74
2	1.04	19
3	1.56	8
4	2.07	5
5	2.59	3

Total lumen output
46 lm

Efficacy
47 lm/W

1W - 50° | UGR 26




H (m)	D (m)	Eav (lx)
1	0.87	37
2	1.75	9
3	2.62	4
4	3.50	2
5	4.37	1

Total lumen output
41 lm

Efficacy
41 lm/W

2W - 20° | UGR 27




H (m)	D (m)	Eav (lx)
1	0.44	141
2	0.89	35
3	1.31	16
4	1.75	9
5	2.19	6

Total lumen output
67 lm

Efficacy
34 lm/W

2W - 30° | UGR 25




H (m)	D (m)	Eav (lx)
1	0.52	97
2	1.04	24
3	1.56	11
4	2.08	6
5	2.60	4

Total lumen output
59 lm

Efficacy
30 lm/W

2W - 50° | UGR 26



H (m)	D (m)	Eav (lx)
1	0.87	48
2	1.74	12
3	2.62	5
4	3.49	3
5	4.36	2

Total lumen output
54 lm


Efficacy
27 lm/W

Product specifications and data are subject to change without warning, due to continue technical upgrades. Images are indicative of the quality and style of the product, but may not represent the precise details of the item you receive. Since we are constantly working to make improvements and for aesthetic reasons, cables and/or electrical elements are often not shown or specified.
For further information please check our website www.dga.it or send us an e-mail to ufficiotecnico@dga.it | Vs 221026

Aria 1


SUGGESTED REMOTE DRIVER

On/off:
CC20-F-350-N / CC20-F-500-N



Ø 55

Multifunction (DALI 2, 0/1-10V, PUSH):
CC25-DM-350-N / CC25-DM-500-N



Ø 55

Other options upon request

Product specifications and data are subject to change without warning, due to continue technical upgrades. Images are indicative of the quality and style of the product, but may not represent the precise details of the item you receive. Since we are constantly working to make improvements and for aesthetic reasons, cables and/or electrical elements are often not shown or specified.
For further information please check our website www.dga.it or send us an e-mail to ufficiotecnico@dga.it | Vs 221026