

Ariel In&Out m dynamic white

Downlights | IP40 | Class III | Dimmable



Fixing
frame




+

Module



+

Interchangeable
accessories



LIGHT SOURCE & OPTIC

Power
9W

Lens
33°/ 52° - interchangeable

Beam Direction
Adjustable:
Tilting +/-90°, rotating +/-355°,
Symmetrical

Material
PMMA

LED quantity
1

Binning
2 MacAdam steps

Color temperature & quality
DIM TO WARM 1800K-3000K CRI>90
TUNABLE WHITE 1800K-4000K CRI>90

Lifetime (Ta 25°)
L80 B50 >88.000 hrs

Ouput
DTW 3000K CRI>90: 918 lm
TW 1800K CRI>90: 626 lm
TW 4000K CRI>90: 976 lm

FIXTURE

Dimensions
Ø 74mm x H 125mm

Material
Aluminium

Module finishes
Warm White (RAL 9010)
White (RAL 9003)
Gray White (RAL 9002)
Gothic Cement (RAL 7033)
Gray (RAL 7012)
Beige Gray (RAL 7006)
Brown (RAL 8019)
Black (RAL 9005)

Filter holder finishes
Gold Chrome
Shiny Chrome
Satin Gold
Satin Nickel
Black

Weight
540gr

Mounting
Recessed: cut out Ø 67mm

Fixing
Fixing frame with spring

Working temperature
-20° / +40°

ELECTRICAL FEATURES

Power supply
Constant current:
250 mA
Typical Vf= 36V


Driver requirement
Remote (not included)

Control
DALI
Push switch
0/1-10 V (DIM TO WARM only)

Ariel In&Out m dynamic white

PHOTOMETRIC DATA (TUNABLE WHITE 1800K CRI>90)

9W - 33° | UGR 19




H (m)	D (m)	Eav (lx)
1	0.65	473
2	1.30	118
3	1.96	53
4	2.61	30
5	3.26	19

Total lumen output
373 lm

Efficacy
41 lm/W

9W - 52° | UGR 20




H (m)	D (m)	Eav (lx)
1	1.19	237
2	2.39	59
3	3.58	26
4	4.78	15
5	5.97	9

Total lumen output
592 lm

Efficacy
66 lm/W

PHOTOMETRIC DATA (TUNABLE WHITE 4000K CRI>90)

9W - 33° | UGR 22




H (m)	D (m)	Eav (lx)
1	0.63	575
2	1.25	189
3	1.88	84
4	2.51	47
5	3.13	30

Total lumen output
420 lm

Efficacy
47 lm/W

9W - 52° | UGR 23




H (m)	D (m)	Eav (lx)
1	1.17	380
2	2.33	95
3	3.50	42
4	4.66	24
5	5.83	15

Total lumen output
668 lm

Efficacy
74 lm/W

PHOTOMETRIC DATA (DIM TO WARM 3000K CRI>90)

9W - 33° | UGR 19




H (m)	D (m)	Eav (lx)
1	0.61	806
2	1.22	202
3	1.83	90
4	2.44	50
5	3.05	32

Total lumen output
575 lm

Efficacy
64 lm/W

9W - 52° | UGR 22



H (m)	D (m)	Eav (lx)
1	1.12	383
2	2.24	96
3	3.36	43
4	4.49	24
5	5.61	15

Total lumen output
629 lm

Efficacy
70 lm/W

Ariel In&Out m dynamic white

INTERCHANGEABLE ACCESSORIES

Optical Filters

Hex louver
Elliptical Filter
Prismatic filter
Softening lens

Lenses

33°/ 52°

Decorative rings

Black
Gold Chrome
Satin Gold
Satin Nickel
Shiny Chrome

INSTALLATION ACCESSORIES


Fixing frame (A01851._0)

Necessary element: please specify always 1 frame for each Fixture in the purchase order

SUGGESTED REMOTE DRIVERS:


DIM TO WARM

Dimmable multifunction driver (DALI2 0/1...10V, PUSH, RIPPLE FREE, AM DIMMING)
CC25-DM-250-N



TUNABLE WHITE

Dimmable multifunction driver (DALI 2 DT8, PUSH, RIPPLE FREE, AM DIMMING):
CC45-D-2x250-N



Other options upon request