

Downlights



IP40

500
700

540 g

Ø67


2

2,5

Ariel In&Out m fixing frame

FIXING FRAME A01293._0

FRAME FINISH
_ See module finish



Ariel In&Out m module

[1] 14° Lens not interchangeable

FIXING FRAME

MODULE



500 / 700mA Lumen Output 3000K	9W 500mA - 900 lm	13W 700mA - 1100 lm
14° Lens [1]	7Q4421._ _ _ _	7Q4422._ _ _ _
18° Lens	784421._ _ _ _	784422._ _ _ _
24° Lens	7G4421._ _ _ _	7G4422._ _ _ _
33° Lens	7E4421._ _ _ _	7E4422._ _ _ _
52° Lens	754421._ _ _ _	754422._ _ _ _

MODULE FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
● H Black	● U1 2200K CRI > 90	● 4 Black	W Without Filter
● M8 Brown	● B2 2400K CRI > 90	● I Gold Chrome	E Elliptical Filter
● G3 Gray	● X 2700K CRI > 90	● 8 Satin Gold	H Hex Louver
● C Gothic Cement	● X1 2700K CRI > 95	● N Satin Nickel	P Prismatic Filter
● G7 Beige Gray	● 6 3000K	● 1 Shiny Chrome	S Softening Lens
● A6 Gray White	● W 3000K CRI > 90		
● S Warm White	● W1 3000K CRI > 95		
○ 7 White	● K 3500K CRI > 90		
	● K1 3500K CRI > 95		
	● D 4000K CRI > 90		



SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
600mA	CC20-F-600-NI	p. 701
700mA	CC20-F-700-NI	p. 702

INTERCHANGEABLE ACCESSORIES



p. 676

EXAMPLE CODE COMPOSITION

