

Downlights

● Plug&Play System



IP40

500
600

530 g

Ø64

P&P

2


2,6

Ariel In&Out F Plug&Play fixing frame


FIXING FRAME A01593._0

FRAME FINISH

- 4 Black
- 3 Gray



Ariel In&Out F Plug&Play module



500 / 600mA Lumen Output 3000K	9W 500mA - 900 lm	11W 600mA - 1000 lm
14° Lens	7Q4625._._._._	7Q4626._._._._
18° Lens	784625._._._._	784626._._._._
24° Lens	7G4625._._._._	7G4626._._._._
33° Lens	7E4625._._._._	7E4626._._._._
52° Lens	754625._._._._	754626._._._._

MODULE FINISH

- H Black
- M8 Brown
- G3 Gray
- C Gothic Cement
- G7 Beige Gray
- A6 Gray White
- S Warm White
- 7 White

CCT

- U1 2200K CRI > 90
- B2 2400K CRI > 90
- X 2700K CRI > 90
- X1 2700K CRI > 95
- 6 3000K
- W 3000K CRI > 90
- W1 3000K CRI > 95
- K 3500K CRI > 90
- K1 3500K CRI > 95
- D 4000K CRI > 90

DECORATIVE RING

- 4 Black
- I Gold Chrome
- 8 Satin Gold
- N Satin Nickel
- 1 Shiny Chrome

OPTICAL FILTER

- W Without Filter
- E Elliptical Filter
- H Hex Louver
- P Prismatic Filter
- S Softening Lens



discover more

SUGGESTED DRIVERS (not included)

500mA	CC10-F-500-SI	p. 700
600mA	CC20-F-600-NI	p. 701
700mA	CC20-F-700-NI	p. 702

INTERCHANGEABLE ACCESSORIES



p. 676



Hole saw
A00830.H0

EXAMPLE CODE COMPOSITION

