

Ariel mR IP55 Wall Washer

Downlights | IP55 | Class III | Dimmable




Fixing
frame



+

Module



LIGHT SOURCE & OPTIC

Power

9W
11W

Lens

Wall washer

Beam Direction

Adjustable:
Tilting $\pm 25^\circ$, rotating $\pm 360^\circ$,
Symmetrical

Material

PMMA

LED quantity

1

Binning

2 MacAdam steps

Color temperature & quality

2200K CRI>90
2400K CRI>90
2700K CRI>90/95
3000K CRI>80/90/95
3500K CRI>90/95
4000K CRI>90

Lifetime (Ta 25°)

L70 >77.000 hrs

Output (3000K CRI>90)

14°: 872 lm / 970 lm
18°/ 24°/ 33°/ 52°: 1020 lm / 1208 lm

FIXTURE

Dimensions

Ø 90mm x Hmax 126mm

Material

Aluminium

Body finishes

Warm White (RAL 9010)
White (RAL 9003)
Gray White (RAL 9002)
Gothic Cement (RAL 7033)
Gray (RAL 7012)
Beige Gray (RAL 7006)
Brown (RAL 8019)
Black (RAL 9005)

Weight

480gr

Mounting

Recessed: cut out Ø 86mm

Fixing

Fixing frame with springs

Working temperature

-20° / $+40^\circ$

ELECTRICAL FEATURES

Power supply

Constant current:
500 mA
600mA
Typical Vf= 18V

Driver requirement



Remote (not included)

Control

On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI

Ariel mR IP55 Wall Washer

PHOTOMETRIC DATA (3000K CRI>90)

9W - WW UGR 33			13W - WW UGR 34		
					
H (m)	D (m)	Eav (lx)	H (m)	D (m)	Eav (lx)
1	1.55	188	1	1.55	243
2	3.10	47	2	3.10	61
3	4.64	21	3	4.65	27
4	6.19	12	4	6.20	15
5	7.74	8	5	7.75	10
Total lumen output 753 lm			Total lumen output 975 lm		
Efficacy 84 lm/W			Efficacy 75 lm/W		

Ariel mR IP55 Wall Washer

INSTALLATION ACCESSORIES


Fixing frame (A01270._0)

Necessary element: please specify always 1 frame for each Fixture in the purchase order

SUGGESTED REMOTE DRIVERS


On/Off :

CC10-F-500-SI



Ø 28


CC23-F-700-SP



Ø 37


Multifunction (DALI 2, 0/1-10V, PUSH RIPPLE FREE, AM DIMMING):

CC15-D-500-S



Ø 30

CC15-D-700-S



Ø 30

Other options upon request