

LIGHT SOURCE

LED quantity	1
Power max	25 W
Total lumen output (3000K)	1015 lm (8°) – 1355 lm (45°)
Efficacy lm/W (3000K)	41 lm/W (8°) – 54 lm/W (45°)
LOR (3000K)	34% (8°) – 44% (45°)
CRI	>80 - >90
LED Temperature (K)	2700K – 3000K – 3000K CRI>90 – 4000K
Average operational life	50.000 hours

OPTIC

Material	Optical glass
Available optics	Zoom optic 8° - 45°
Beam direction	Adjustable +/-103°, Rotating +/-355°
Flux symmetry	Symmetrical
Accessories	-

LED FIXTURE

Material	Aluminum
Finish	Painted (Black, White, All White)
Available finishes	Black, White, All White
IP Rate	IP40
Working Temperature	-20° ÷ +40°
Accessories	-

ELECTRICAL FEATURES

Driver	Remote
Dimmable	Push, 1-10V, DALI
For emergency lighting	Upon Request
Connection	In series at 700mA
Class	III

MECHANICAL FEATURES

Dimensions (mm)	Ø80 x 140 (cylinder only)
Weight	1020 gr
Mounting	Wall, Ceiling
Cut-out (mm)	Ø66
Use	Indoor

NOTES

