


Cometa Q4

Linear System | IP40 | Class III | Dimmable



Integrated Fixing*

Magnetic fixing Double sided tape



LIGHT SOURCE & OPTIC

Power

4W
8W
14W

Covers

Milky cover (32°)
Black ghost cover (80%)

Beam Direction

Fixed, Symmetrical

Material

Polycarbonate

LED quantity

118/m

Binning

2 MacAdam steps

Color temperature & quality

2200K CRI>80
2500K CRI>80
2700K CRI>90
3000K CRI>90
3500K CRI>90
4000K CRI>90

Lifetime (Ta 25°)

L85 >95.000 hrs

FIXTURE

Dimensions

D 4,5mm x H 4,5mm x L:
007 013 019 025 031 037 043 049 054 060
066 072 078 084 090 096 101 107 113 119
125 131 137 143 148 154 160 166 172 178
184 190 196

Material

Aluminium

Body finishes

Black
Gray

Weight

40gr/m

End caps

Aluminium

Mounting

On surface

Fixing*

Magnetic fixing
Double sided tape
Without fixing (see accessories)

Working temperature

-20° / +40°

ELECTRICAL FEATURES

Power supply

Constant tension: 24 Vdc

Driver

Remote (not included)

Control

On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI

Cable exit

Cap exit




In&Out cap exit



Cometa Q4


PHOTOMETRIC DATA (3000K CRI>90 - Milky cover)

4W/m - 110° | UGR 28




H (m)	D (m)	Eav (lx)
1	2.81	14
2	5.63	4
3	8.44	2
4	11.25	1
5	14.06	1

8W/m - 110° | UGR 29



H (m)	D (m)	Eav (lx)
1	2.98	25
2	5.96	6
3	8.95	3
4	11.93	2
5	14.91	1

14W/m - 110° | UGR 30



H (m)	D (m)	Eav (lx)
1	2.99	36
2	5.97	9
3	8.96	4
4	11.94	2
5	14.93	1

Total lumen output
257 lm

Efficacy
64 lm/W

Total lumen output
487 lm

Efficacy
61 lm/W

Total lumen output
716 lm


Efficacy
51 lm/W

Cometa Q4

INSTALLATION ACCESSORIES


Magnetic brackets

Only for Cometa Q4 without fixing




Brackets and screws

Only for Cometa Q4 without fixing




Iron plate (A01742.H0)

Only for Cometa Q4 with magnetic fixing



Iron plate (A01745.H0)


Only for Cometa Q4 with magnetic brackets



SUGGESTED REMOTE DRIVERS


On/Off :

CV70-F-24-N



Multifunction (DALI 2, 0/1-10V, PUSH):

CV75-DM-24-NI



Other options upon request