



Cometa Q8

Linear System | IP40 | Class III | Dimmable



Integrated Fixing*

Magnetic fixing Double sided tape



LIGHT SOURCE & OPTIC

Power

8W
12W
16W
19W
23W

Covers

Transparent cover (6%)
Opal cover (25°)
Milky cover (32°)
Black ghost cover (80%)

Beam Direction

Fixed, Symmetrical

Material

Polycarbonate

LED quantity

233

Binning

2 MacAdam steps

Color temperature & quality

2200K CRI>80
2500K CRI>80
2700K CRI>90
3000K CRI>90
3500K CRI>90
4000K CRI>90

Lifetime

L85 >95.000 hrs

FIXTURE

Dimensions

D 8mm x H 8mm x L:

004 007 010 013 016 019 022 025 028 031
034 037 040 043 046 049 052 055 058 061
064 067 070 073 076 079 082 085 088 091
094 097 100 103 106 109 112 115 118 121
124 127 130 133 136 139 142 145 148 151
154 157 160 163 166 169 172 175 178 181
184 187 190 193 196 199 202 205 208 211
214 217 220 223 226 229 232 235 238 241
244 247 250 253 256 259 262 265 268 271
274 277 280 283 286 289 292 295 298

Material

Aluminium

Body finishes

Black
Gray

Weight

100gr/m

End caps

Aluminium
Transparent

Mounting

On surface

Fixing*

Magnetic fixing
Double sided tape
Without fixing (see accessories)

Working temperature

-20° / +40°

ELECTRICAL FEATURES

Power supply

Constant tension: 24 Vdc

Driver

Remote (not included)

Control

On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI

Cable exit

Cap exit

In&Out cap exit

Left side exit

In&Out side exit

Right side exit

Back exit


Back in&out exit



Cometa Q8

PHOTOMETRIC DATA (3000K CRI>90 - Opal cover)

8W/m - 105° | UGR 27




H (m)	D (m)	Eav (lx)
1	2.55	34
2	5.09	8
3	7.64	4
4	10.18	2
5	12.73	1

Total lumen output
490 lm

Efficacy
61 lm/W

12W/m - 105° | UGR 28




H (m)	D (m)	Eav (lx)
1	2.54	52
2	5.09	13
3	7.63	6
4	10.18	3
5	12.72	2

Total lumen output
763 lm

Efficacy
63 lm/W

16W/m - 105° | UGR 29




H (m)	D (m)	Eav (lx)
1	2.56	65
2	5.11	16
3	7.67	7
4	10.23	4
5	12.78	3

Total lumen output
938 lm

Efficacy
58 lm/W

19W/m - 105° | UGR 30




H (m)	D (m)	Eav (lx)
1	2.53	79
2	5.07	20
3	7.60	9
4	7.60	5
5	10.14	3

Total lumen output
1130 lm

Efficacy
60 lm/W

23W/m - 105° | UGR 31



H (m)	D (m)	Eav (lx)
1	2.54	94
2	5.09	23
3	7.63	10
4	10.17	6
5	12.72	4


Total lumen output
1365 lm

Efficacy
59 lm/W

Cometa Q8

PHOTOMETRIC DATA (3000K CRI>90 - Milky cover)

8W/m - 110° | UGR 27




H (m)	D (m)	Eav (lx)
1	2.95	22
2	5.91	6
3	8.86	2
4	11.82	1
5	14.77	1

Total lumen output
438 lm

Efficacy
55 lm/W

12W/m - 110° | UGR 28




H (m)	D (m)	Eav (lx)
1	2.95	35
2	5.89	9
3	8.84	4
4	11.78	2
5	14.73	1

Total lumen output
663 lm

Efficacy
57 lm/W

16W/m - 110° | UGR 29




H (m)	D (m)	Eav (lx)
1	2.95	43
2	5.89	11
3	8.84	5
4	11.79	3
5	14.74	2

Total lumen output
840 lm

Efficacy
53 lm/W

19W/m - 110° | UGR 30




H (m)	D (m)	Eav (lx)
1	2.95	52
2	5.89	13
3	8.84	6
4	11.79	3
5	14.73	2

Total lumen output
1020 lm

Efficacy
54 lm/W

23W/m - 110° | UGR 31



H (m)	D (m)	Eav (lx)
1	2.96	62
2	5.91	15
3	8.87	7
4	11.83	4
5	14.78	2

Total lumen output
1220 lm


Efficacy
53 lm/W

Cometa Q8

INSTALLATION ACCESSORIES


Magnetic brackets

Only for Cometa Q8 without fixing




Brackets and screws

Only for Cometa Q8 without fixing




Mounting clips

Only for Cometa Q8 without fixing



Iron plate (A01744.H0)


Only for Cometa Q8 with magnetic fixing



SUGGESTED REMOTE DRIVERS


On/Off :

CV70-F-24-N



Multifunction (DALI 2, 0/1-10V, PUSH):

CV75-DM-24-NI



Other options upon request