

Continuum i IP67 Louver

DGA

Linear with Lenses



discover more




Continuum i IP67 Louver



Linear with Lenses



| | | | | | | | | | | | | |
|------|------|-----|--|--|-------|-----|-------|--------|--------|--------|--------|---|
| | | | | | | | | | | | | |
| IP67 | WIPS | 24V | | | IK 10 | 1 m | 890 g | 1660 g | 2440 g | 3210 g | 3980 g | 2 |



Lumen Output 3000K
30W/m - 10° Lens: 2500 lm/m


| FINISH | CCT |
|-----------|--------------------|
| ● 4 Black | ● U 2200K |
| | ● Y 2700K |
| | ● W 3000K CRI > 90 |
| | ● 6 3000K |
| | ● 9 4000K |
| | ● 8 TUNABLE WHITE |

Continuum i IP67 Louver

| 24V | 9W | 18W | 27W | 36W |
|-----------------|------------|------------|------------|------------|
| Lenght | 30 cm | 60 cm | 90 cm | 120 cm |
| 10° Lens | 734462._ _ | 734463._ _ | 734464._ _ | 734465._ _ |
| 25° Lens | 764462._ _ | 764463._ _ | 764464._ _ | 764465._ _ |
| 40° Lens | 744462._ _ | 744463._ _ | 744464._ _ | 744465._ _ |
| 60° Lens | 754462._ _ | 754463._ _ | 754464._ _ | 754465._ _ |
| Elliptical Lens | 774462._ _ | 774463._ _ | 774464._ _ | 774465._ _ |



| | | | | | | | | | | | | |
|------|------|------|--|--|-------|-----|--------|--------|--------|--------|--------|---|
| | | | | | | | | | | | | |
| IP67 | WIPS | 230V | | | IK 10 | 1 m | 1260 g | 2200 g | 3040 g | 3870 g | 4700 g | 2 |



Lumen Output 3000K
30W/m - 10° Lens: 2500 lm/m

| FINISH | CCT |
|-----------|--------------------|
| ● 4 Black | ● U 2200K |
| | ● Y 2700K |
| | ● W 3000K CRI > 90 |
| | ● 6 3000K |
| | ● 9 4000K |

Continuum i IP67 Louver 230V

| 220-240Vac | 11W | 21W | 30W | 40W |
|-----------------|------------|------------|------------|------------|
| Lenght | 30 cm | 60 cm | 90 cm | 120 cm |
| 10° Lens | 734466._ _ | 734467._ _ | 734468._ _ | 734469._ _ |
| 25° Lens | 764466._ _ | 764467._ _ | 764468._ _ | 764469._ _ |
| 40° Lens | 744466._ _ | 744467._ _ | 744468._ _ | 744469._ _ |
| 60° Lens | 754466._ _ | 754467._ _ | 754468._ _ | 754469._ _ |
| Elliptical Lens | 774466._ _ | 774467._ _ | 774468._ _ | 774469._ _ |

Continuum i IP67 louver 230V DALI

| 220-240Vac | 11W | 21W | 30W | 40W |
|-----------------|------------|------------|------------|------------|
| Lenght | 30 cm | 60 cm | 90 cm | 120 cm |
| 10° Lens | 734470._ _ | 734471._ _ | 734472._ _ | 734473._ _ |
| 25° Lens | 764470._ _ | 764471._ _ | 764472._ _ | 764473._ _ |
| 40° Lens | 744470._ _ | 744471._ _ | 744472._ _ | 744473._ _ |
| 60° Lens | 754470._ _ | 754471._ _ | 754472._ _ | 754473._ _ |
| Elliptical Lens | 774470._ _ | 774471._ _ | 774472._ _ | 774473._ _ |

SUGGESTED DRIVERS (not included)

| | | |
|----------|---------------|--------|
| 24Vdc | CV70-F-24-N | p. 708 |
| 24Vdc TW | CV100-L-24-NL | p. 707 |

ACCESSORIES

| | | | | | |
|--|--|--|---|-------------------------------|------------------------------------|
| | | | | | |
| Recessed box L 30 cm in Stainless Steel AISI 316L | Recessed box L 60 cm in Stainless Steel AISI 316L | Recessed box L 90 cm in Stainless Steel AISI 316L | Recessed box L 120 cm in Stainless Steel AISI 316L | Watertight connector 24Vdc | Watertight connector 220-240Vac |
| A01209.60 | A01210.60 | A01211.60 | A01212.60 | A00357.40 | A01023.40 |
| Recessed box for Continuum i IP67 louver 24V | Recessed box for Continuum i IP67 louver 230V | | | | p. 682 |