



IP68 Recessed



350 / 500mA Lumen Output 3000K	1W 350mA - 120 lm	2W 500mA - 170 lm	3W 350mA - 100 lm
10° Lens	730920.6 _	730921.6 _	
30° Lens	760920.6 _	760921.6 _	
40° Lens	740920.6 _	740921.6 _	
Frosted Glass	710920.6 _	710921.6 _	710922.6 _
Transparent Glass	720920.6 _	720921.6 _	720922.6 _
Elliptical Lens	770920.6 _	770921.6 _	

FINISH

- 6 Stainless Steel
AISI 316L

CCT

- U 2200K
- Y 2700K
- 6 3000K
- 9 4000K
- 1 5000K


12V Lumen Output 3000K	1,5W 12Vdc - 120 lm	2W 12Vdc - 170 lm	4W 12Vdc - 100 lm
10° Lens	734761.6 _	734762.6 _	
30° Lens	764761.6 _	764762.6 _	
40° Lens	744761.6 _	744762.6 _	
Frosted Glass	714761.6 _	714762.6 _	714763.6 _
Transparent Glass	724761.6 _	724762.6 _	724763.6 _
Elliptical Lens	774761.6 _	774762.6 _	




SUGGESTED DRIVERS (not included)

350mA	CC14-F-350-PI	p. 704
500mA	CC14-F-500-PI	p. 704
12Vdc	CV20-F-12-PI	p. 706


ACCESSORIES




Aluminum recessed box
A00231.30



Plastic recessed box
A00249.40



Stainless Steel IP68 recessed box
A01117.60



Watertight connector p. 682
A00357.40

EXAMPLE CODE COMPOSITION

123456 CCT FINISH