

GIOVE 3S R



IP67



Class III



Incasso a parete, pavimento
Wall, floor recessed



WIPS - Water Infiltration Protection System



Carrabile 2000 kg
Drive over up to 2000 kg



Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)



Collegare in serie 350mA
Connect in series at 350mA



Collegare in parallelo 24Vdc
Connect in parallel at 24Vdc



600 gr



Altamente riciclabile
Highly recyclable




Orientabile +/- 20°
Versione con nido d'ape
Alta efficienza

Adjustable +/- 20°
Honeycomb version
High efficiency

GIOVE 3S R

	3W 350mA	3W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	300lm	300lm		
15° Lens	7A3170._.	7A3171._.	3 Grigio - Gray	U 2200K
30° Lens	763170._.	763171._.	4 Nero - Black	Y 2700K
60° Lens	753170._.	753171._.	6 Acciaio Inox Stainless Steel AISI 316L	6 3000K
Vetro satinato Frosted glass	713170._.	713171._.		9 4000K
Lente ellittica Elliptical lens	773170._.	773171._.		



GIOVE 3S R

CON NIDO D'APE - WITH HEX LOUVER

	3W 350mA	3W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	300lm	300lm		
15° Lens	7A3560._.	7A3561._.	3 Grigio - Gray	U 2200K
30° Lens	763560._.	763561._.	4 Nero - Black	Y 2700K
60° Lens	753560._.	753561._.	6 Acciaio inox Stainless Steel AISI 316L	6 3000K
Vetro satinato Frosted glass	713560._.	713561._.		9 4000K
Lente ellittica Elliptical lens	773560._.	773561._.		

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA CC20-F-350-N
24Vdc CV20-F-24-N

ACCESSORI
ACCESSORIES



Controcassa
Recessed box
A00130.40



Connettore stagno
Watertight connector
A00387.40



Ø 76 mm

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH