



Macro H350 with hex louver

Bollards | IP67 | Class III | Dimmable



LIGHT SOURCE & OPTIC

Power

3W
6W (7W-24Vdc)
9W

Lens

3°
10°
30°
50°

Beam Direction

Adjustable:
Tilting +/-100°, rotating +/-355°,
Symmetrical

Material

PMMA + glass

LED quantity

1

Binning

2 MacAdam steps

Color temperature & quality

2200K CRI>80
2700K CRI>80
3000K CRI>80/90
3500K CRI>80
4000K CRI>90

Lifetime

(L90) >60.000 hrs

FIXTURE

Dimensions

70mm x 106mm x H 350mm

Material

Aluminium

Body finishes

Black
Moka
Anthracite gray
Olive green
Gray

Weight

570gr

Mounting

On surface

Fixing

Applique
Via Installation accessories

Working temperature

-20° / +40°

ELECTRICAL FEATURES

Power supply

Constant current:
900 mA (3W)
500 mA (6W)
700mA (9W)
Typical Vf= 3V (3W)
Typical Vf= 12V (6/9W)
Constant tension:
24Vdc (3/7/9W)

Driver requirement

Remote (not included)

Control

On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI


Feature

Water Infiltration Protection System

Macro H350 with hex louver

PHOTOMETRIC DATA (3000K CRI>90)

3W - 3° | UGR 10




H (m)	D (m)	Eav (lx)
1	0.10	1947
2	0.20	487
3	0.30	216
4	0.40	122
5	0.49	78

Total lumen output
124 lm

Efficacy
41 lm/W

6W - 10° | UGR 3




H (m)	D (m)	Eav (lx)
1	0.26	2199
2	0.52	550
3	0.78	244
4	1.04	137
5	1.29	88

Total lumen output
377 lm

Efficacy
63 lm/W
54 lm/W(24Vdc)

6W - 30° | UGR 7




H (m)	D (m)	Eav (lx)
1	0.39	838
2	0.78	209
3	1.16	93
4	1.55	52
5	1.94	34

Total lumen output
242 lm

Efficacy
40 lm/W
35 lm/W(24Vdc)

6W - 50° | UGR 8




H (m)	D (m)	Eav (lx)
1	0.55	440
2	1.11	110
3	1.66	49
4	2.21	28
5	2.76	18

Total lumen output
211 lm

Efficacy
35 lm/W
30 lm/W(24Vdc)

9W - 10° | UGR 5




H (m)	D (m)	Eav (lx)
1	0.26	2865
2	0.52	716
3	0.78	318
4	1.03	179
5	1.29	115

Total lumen output
377 lm

Efficacy
42 lm/W

9W - 30° | UGR 8




H (m)	D (m)	Eav (lx)
1	0.39	1103
2	0.79	276
3	1.18	123
4	1.57	69
5	1.97	44

Total lumen output
320 lm

Efficacy
43 lm/W

9W - 50° | UGR 9



H (m)	D (m)	Eav (lx)
1	0.56	585
2	1.11	146
3	1.67	65
4	2.22	37
5	2.78	23


Total lumen output
280 lm

Efficacy
31 lm/W


Macro H350 with hex louver

INTERCHANGEABLE ACCESSORIES

Low glare visor (A00519._0)




Low glare snoot (A00848._0)




INSTALLATION ACCESSORIES


Anchor for concrete (A00943.60)



Stainless Steel stake (A00852.60)




Watertight connector (A00387.40)




SUGGESTED REMOTE DRIVERS

On/Off :

CC14-F-500/700/900-PI




CV30-F-24-PI




Multifunction (DALI 2, 0/1-10V, PUSH RIPPLE FREE, AM DIMMING):


CC20-D-350-P




CV25-D-500-P



CV30-D-700-P



CV25-D-24-PI



Other options upon request