


Bollards



Micro H350

350mA	3W
Lumen Output 3000K	350mA - 270 lm
15° Lens	7A4104._ _
30° Lens	764104._ _
60° Lens	754104._ _
Frosted Glass	714103._ _
Elliptical Lens	774104._ _


24V	4W
Lumen Output 3000K	24Vdc - 270 lm
15° Lens	7A4732._ _
30° Lens	764732._ _
60° Lens	754732._ _
Frosted Glass	714732._ _
Elliptical Lens	774732._ _

Micro H350 with hex louver

350mA	3W
Lumen Output 3000K	350mA - 190 lm
15° Lens	7A4106._ _
30° Lens	764106._ _
60° Lens	754106._ _
Frosted Glass	714105._ _
Elliptical Lens	774106._ _

24V	4W
Lumen Output 3000K	24Vdc - 190 lm
15° Lens	7A4733._ _
30° Lens	764733._ _
60° Lens	754733._ _
Frosted Glass	714733._ _
Elliptical Lens	774733._ _

FINISH	CCT
4 Black	U 2200K
MF Moka	Y 2700K
4A Anthracite Gray	6 3000K
VB Olive Green	W 3000K CRI > 90
3 Gray	9 4000K



SUGGESTED DRIVERS (not included)

350mA	CC14-F-350-PI	p. 704
24Vdc	CV30-F-24-PI	p. 708

ACCESSORIES

35
Ø39
9

Low glare visor
A00846._0

35
Ø39
35

Low glare snoot
A00847._0

180
138
57

Anchor for concrete
A00942.60

Ø55
230

Stainless Steel stake
A00851.60

37
22
36,5

Watertight connector p. 682
A00387.40

EXAMPLE CODE COMPOSITION

123456.	CCT	FINISH
---------	-----	--------