

LIGHT SOURCE & OPTIC

- Power**
2.5W
- Lens**
10°/25°/40°/60°
- Beam Direction**
Adjustable: +/-90° Rotating +/-355°
Symmetrical
- Material**
PMMA
- LED quantity**
1
- Binning**
2 MacAdam steps
- Color temperature & quality**
2200K
2700K CRI>90
3000K CRI>90
4000K CRI>90
5000K CRI>90
- Lifetime**
(L90) >60.000 hrs





FIXTURE

- Dimensions**
Ø 20mm x H 49mm (cylinder)
- Material**
Aluminium
- Body finishes**
Black
Fir Green (RAL6009)
Bright Brown
Massive Brass
Grey
Stainless Steel 316L
- Weight**
40gr
- Mounting**
On surface
- Fixing**
Applique
Stake
Tree strap mounting
Stake H350
Bollard H350
- Working temperature**
-20° / +40°

ELECTRICAL FEATURES


- Power supply**
Main Voltage:
700 mA
- Driver requirement**
Remote (not included)
- Control**
On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI

PHOTOMETRIC DATA (3000K CRI>90)


2.5W - 10° UGR 12.1	2.5W - 25° UGR 14.3	2.5W - 40° UGR 20.9	2.5W - 60° UGR 23.8																																																																								
																																																																											
<table><tr><th>H (m)</th><th>D (m)</th><th>Eav (lx)</th></tr><tr><td>1</td><td>0.25</td><td>1396</td></tr><tr><td>2</td><td>0.50</td><td>349</td></tr><tr><td>3</td><td>0.75</td><td>155</td></tr><tr><td>4</td><td>0.99</td><td>87</td></tr><tr><td>5</td><td>1.24</td><td>56</td></tr></table>	H (m)	D (m)	Eav (lx)	1	0.25	1396	2	0.50	349	3	0.75	155	4	0.99	87	5	1.24	56	<table><tr><th>H (m)</th><th>D (m)</th><th>Eav (lx)</th></tr><tr><td>1</td><td>0.37</td><td>561</td></tr><tr><td>2</td><td>0.73</td><td>140</td></tr><tr><td>3</td><td>1.10</td><td>62</td></tr><tr><td>4</td><td>1.46</td><td>35</td></tr><tr><td>5</td><td>1.83</td><td>22</td></tr></table>	H (m)	D (m)	Eav (lx)	1	0.37	561	2	0.73	140	3	1.10	62	4	1.46	35	5	1.83	22	<table><tr><th>H (m)</th><th>D (m)</th><th>Eav (lx)</th></tr><tr><td>1</td><td>0.63</td><td>255</td></tr><tr><td>2</td><td>1.27</td><td>64</td></tr><tr><td>3</td><td>1.90</td><td>28</td></tr><tr><td>4</td><td>2.53</td><td>16</td></tr><tr><td>5</td><td>3.17</td><td>10</td></tr></table>	H (m)	D (m)	Eav (lx)	1	0.63	255	2	1.27	64	3	1.90	28	4	2.53	16	5	3.17	10	<table><tr><th>H (m)</th><th>D (m)</th><th>Eav (lx)</th></tr><tr><td>1</td><td>0.93</td><td>110</td></tr><tr><td>2</td><td>1.85</td><td>28</td></tr><tr><td>3</td><td>2.78</td><td>12</td></tr><tr><td>4</td><td>3.71</td><td>7</td></tr><tr><td>5</td><td>4.64</td><td>4</td></tr></table>	H (m)	D (m)	Eav (lx)	1	0.93	110	2	1.85	28	3	2.78	12	4	3.71	7	5	4.64	4
H (m)	D (m)	Eav (lx)																																																																									
1	0.25	1396																																																																									
2	0.50	349																																																																									
3	0.75	155																																																																									
4	0.99	87																																																																									
5	1.24	56																																																																									
H (m)	D (m)	Eav (lx)																																																																									
1	0.37	561																																																																									
2	0.73	140																																																																									
3	1.10	62																																																																									
4	1.46	35																																																																									
5	1.83	22																																																																									
H (m)	D (m)	Eav (lx)																																																																									
1	0.63	255																																																																									
2	1.27	64																																																																									
3	1.90	28																																																																									
4	2.53	16																																																																									
5	3.17	10																																																																									
H (m)	D (m)	Eav (lx)																																																																									
1	0.93	110																																																																									
2	1.85	28																																																																									
3	2.78	12																																																																									
4	3.71	7																																																																									
5	4.64	4																																																																									
<div>Total lumen output</div> <div>123 lm</div>	<div>Total lumen output</div> <div>111 lm</div>	<div>Total lumen output</div> <div>112 lm</div>	<div>Total lumen output</div> <div>80 lm</div>																																																																								
<div>Efficacy</div> <div>52 lm/W</div>	<div>Efficacy</div> <div>45 lm/W</div>	<div>Efficacy</div> <div>45 lm/W</div>	<div>Efficacy</div> <div>32 lm/W</div>																																																																								

INTERCHANGEABLE ACCESSORIES

Low glare visor: A01445._0




Low glare tube visor: A01444._0




INSTALLATION ACCESSORIES

Micro watertight connector: A00357.40




SUGGESTED REMOTE DRIVER

On/off:
CC14-F-700-PI



Multifunction (DALI 2, 0/1-10V, PUSH):
CC20-M-700-P



Other options upon request