
Nano Tini i

Indoor | Small recessed | IP40 | Class III | Dimmable







LIGHT SOURCE & OPTIC

Power
1W

Lens
20°
30°
50°

Beam Direction
Fixed
Symmetrical

Material
PMMA

LED quantity
1

Binning
2 MacAdam steps

Color temperature & quality
2200K CRI>80
2700K CRI>90
3000K CRI>90
3500K CRI>90
4000K CRI>90

Lifetime (Ta 25°)
L_{85} >55.000 hrs

Source Flux (3000K CRI>90)
86 lm @ 350 mA

FIXTURE

Dimensions
Ø 13,5 mm x H 13 mm

Material
Aluminium
Massive Brass

Body finishes
Black
Massive Brass
Gold Chrome
Gray
Shiny Chrome
White (RAL 9003)

Weight
8 gr

Mounting
Recessed: cut out Ø 10,5 mm

Fixing
O-ring

Working temperature
-20° / +40°

ELECTRICAL FEATURES

Power supply
Constant current:
350 mA
Typical Vf= 3V

Driver requirement
Remote (not included)

Control
On/off
Push switch
Phase Cut
0/1-10 V
Casambi
DALI


Feature
Side exit cable

Product specifications and data are subject to change without warning, due to continue technical upgrades. Images are indicative of the quality and style of the product, but may not represent the precise details of the item you receive. Since we are constantly working to make improvements and for aesthetic reasons, cables and/or electrical elements are often not shown or specified.
For further information please check our website www.dga.it or send us an e-mail to ufficiotecnico@dga.it | Vs 291026

Nano Tini i

PHOTOMETRIC DATA (3000K CRI>90)

1W - 20° | UGR 24




H (m)	D (m)	Eav (lx)
1	0.45	107
2	0.90	27
3	1.34	12
4	1.79	7
5	2.24	4

Total lumen output
51 lm

Efficacy
51 lm/W

1W - 30° | UGR 24




H (m)	D (m)	Eav (lx)
1	0.51	74
2	1.01	19
3	1.52	8
4	2.03	5
5	2.54	3

Total lumen output
46 lm

Efficacy
46 lm/W

1W - 50° | UGR 25



H (m)	D (m)	Eav (lx)
1	0.84	37
2	1.68	9
3	2.52	4
4	3.36	2
5	4.20	1

Total lumen output
41 lm


Efficacy
41 lm/W

Product specifications and data are subject to change without warning, due to continue technical upgrades. Images are indicative of the quality and style of the product, but may not represent the precise details of the item you receive. Since we are constantly working to make improvements and for aesthetic reasons, cables and/or electrical elements are often not shown or specified.
For further information please check our website www.dga.it or send us an e-mail to ufficiotecnico@dga.it | Vs 291026

Nano Tini i


SUGGESTED REMOTE DRIVER

On/off:
CC20-F-350-N



Ø 55

Multifunction (DALI 2, 0/1-10V, PUSH):
CC25-DM-350-N



Ø 55

Other options upon request

Product specifications and data are subject to change without warning, due to continue technical upgrades. Images are indicative of the quality and style of the product, but may not represent the precise details of the item you receive. Since we are constantly working to make improvements and for aesthetic reasons, cables and/or electrical elements are often not shown or specified.
For further information please check our website www.dga.it or send us an e-mail to ufficiotecnico@dga.it | Vs 291026