

Recessed Lights

● Plug&Play System



IP67

WIPS

350

24V

12°


1 m

720 g

P&P

2

2,7



	350mA Lumen Output 3000K	12W 350mA - 1200 lm
12° Lens	7Q4554.	__ _ _ _
18° Lens	784554.	__ _ _ _
24° Lens	7G4554.	__ _ _ _
33° Lens	7E4554.	__ _ _ _
52° Lens	754554.	__ _ _ _

	24V Lumen Output 3000K	14W 24Vdc - 1200 lm
12° Lens	7Q4681.	__ _ _ _
18° Lens	784681.	__ _ _ _
24° Lens	7G4681.	__ _ _ _
33° Lens	7E4681.	__ _ _ _
52° Lens	754681.	__ _ _ _

FINISH	CCT	DECORATIVE RING	OPTICAL FILTER
4 Black	U1 2200K CRI > 90	4 Black	W Without Filter
3 Gray	B2 2400K CRI > 90	1 Gold Chrome	E Elliptical Filter
6 Stainless Steel AISI 316L	X 2700K CRI > 90	8 Satin Gold	H Hex Louver
	6 3000K	N Satin Nickel	P Prismatic Filter
	W 3000K CRI > 90	1 Shiny Chrome	S Softening Lens
	K 3500K CRI > 90		
	D 4000K CRI > 90		

discover more


SUGGESTED DRIVERS (not included)

350mA	CC14-F-350-PI	p. 704
24Vdc	CV30-F-24-PI	p. 708


ACCESSORIES



INTERCHANGEABLE ACCESSORIES
p. 677



Aluminum recessed box
A01417.40



Watertight connector p. 682
A00387.40

EXAMPLE CODE COMPOSITION

