

Downlights



IP40

400

960 g

Ø86
[3 3/8"]

SD
CM

TM
66

IC

UL
LISTED

Saturno In&Out F fixing frame

FIXING FRAME A01551._0


FRAME FINISH

● 4

Black

● 3

Gray



Saturno In&Out F module

400mA Lumen Output 3000K	14W 400mA - 1550 lm
12° Lens [1]	7Q4604.____-UL
18° Lens	784604.____-UL
24° Lens	7G4604.____-UL
33° Lens	7E4604.____-UL
52° Lens	754604.____-UL

MODULE FINISH

● H

Black

● M8

Brown

● G3

Gray

● C

Gothic Cement

● G7

Beige Gray

● A6

Gray White

● S

Warm White

○ 7

White

CCT

● U1

2200K CRI > 90

● B2

2400K CRI > 90

● X

2700K CRI > 90

● X1

2700K CRI > 95

● 6

3000K

● W

3000K CRI > 90

● W1

3000K CRI > 95

● K

3500K CRI > 90

● K1

3500K CRI > 95

● D

4000K CRI > 90

DECORATIVE RING

● 4

Black

● I

Gold Chrome

● 8

Satin Gold

● N

Satin Nickel

● 1

Shiny Chrome

OPTICAL FILTER

W

Without Filter

E

Elliptical Filter

H

Hex Louver

P

Prismatic Filter

S

Softening Lens

[1] 12° Lens not interchangeable

FIXING FRAME

MODULE

discover more

SUGGESTED DRIVERS (not included)

400mA CC36-R-400-NF p. 244

INTERCHANGEABLE ACCESSORIES

Hole saw
A00833.H0

p. 235

EXAMPLE CODE COMPOSITION

123456.____-UL

OPTICAL FILTER

DECORATIVE RING

CCT

MODULE FINISH