






TINI B 24V

-  IP40
-  Class III
-  Binario a parete, soffitto
Wall, ceiling mounting track
-  Collegare a binario a bassa tensione 24Vdc
Connect to 24Vdc low voltage track
-  100 gr
-  Altamente riciclabile
Highly recyclable



TINI B 24V

	3W 24Vdc		Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	300lm			
 15° Lens	7A4542._ _		<ul style="list-style-type: none"> <input type="checkbox"/> 7 Bianco - White <input type="checkbox"/> B Bronzo Scuro Dark Bronze <input type="checkbox"/> H Nero - Black 	<ul style="list-style-type: none"> <input type="checkbox"/> U 2200K <input type="checkbox"/> Y 2700K <input type="checkbox"/> X 2700K CRI > 90 <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> 9 4000K <input type="checkbox"/> 1 5000K
 30° Lens	764542._ _			
 60° Lens	754542._ _			
 Lente ellittica Elliptical lens	774542._ _			



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

24Vdc CV70-F-24-N



Binari 24Vdc e accessori
24Vdc tracks and accessories

EXAMPLE CODE COMPOSITION
123456.

