

Tono B Micro

Low Voltage Track Projectors




IP40

24V  
48V

SD  
CM

190 g

2



Tono B Micro

 24-48Vdc Lumen Output 3000K	3W 24-48Vdc - 250 lm	7W 24-48Vdc - 520 lm	10W 24-48Vdc - 700 lm
3° Lens	7T4797. _ _ _		
10° Lens		734798. _ _ _	734799. _ _ _
30° Lens		764798. _ _ _	764799. _ _ _
50° Lens		7D4798. _ _ _	7D4799. _ _ _

**FINISH**

● H

Black

● B

Dark Bronze

○ 7

White

**CCT**

● Y

2700K

● 6

3000K

● W

3000K CRI > 90

● 9

4000K

● 1

5000K

**DIMMING**

F

ON-OFF

D

DALI

M

Broadcast

Tono B Micro with hex louver

 24-48Vdc Lumen Output 3000K	3W 24-48Vdc - 170 lm	7W 24-48Vdc - 410 lm	10W 24-48Vdc - 540 lm
3° Lens	7T4800. _ _ _		
10° Lens		734801. _ _ _	734802. _ _ _
30° Lens		764801. _ _ _	764802. _ _ _
50° Lens		7D4801. _ _ _	7D4802. _ _ _



SUGGESTED DRIVERS (not included)

24Vdc	CV70-F-24-N	p. 707
48Vdc	CV150-F-48-N	p. 709

TRACKS ACCESSORIES

Micro track and accessories p. 684

EXAMPLE CODE COMPOSITION

