









GEMMA 35 IP68













-  IP68
-  Class III
-  Incasso a parete, pavimento
Wall, floor recessed
-  WIPS - Water Infiltration Protection System
-  Cavo in neoprene 500 cm
500 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in serie 350mA o 500mA
Connect in series at 350mA or 500mA
-  200 gr
-  Altamente riciclabile
Highly recyclable




Ampia gamma di ottiche
Due tipologie di controcassa
Dimensioni compatte

Wide range of optics
Two types of recessed box
Compact size

GEMMA 35 IP68

	1W 350mA	2W 500mA	3W 350mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	100lm	150lm	300lm		
 10° Lens	730920.6 _	730921.6 _		 6 Acaccia Inox Stainless Steel AISI 316L	 U 2200K  Y 2700K  6 3000K  9 4000K  1 5000K
 30° Lens	760920.6 _	760921.6 _			
 40° Lens	740920.6 _	740921.6 _			
 Vetro trasparente Transparent glass	720920.6 _	720921.6 _	720922.6 _		
 Vetro satinato Frosted glass	710920.6 _	710921.6 _	710922.6 _		
 Lente ellittica Elliptical lens	770920.6 _	770921.6 _			



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA **CC20-F-350-N**
500mA **CC20-F-500-N**

ACCESSORI
ACCESSORIES



Controcassa
Recessed box
A00231.30




Controcassa
Recessed box
A00249.40



Controcassa IP68
AISI 316L
IP68 Recessed box
A01117.60



Micro connettore stagno
Micro watertight connector
A00357.40



EXAMPLE CODE COMPOSITION
123456

LED COLOUR
FINISH