

















TRIUM P IP67

-  IP67
-  Class III 24Vdc
-  Class II 220-240Vac
-  Montaggio a parete, soffitto, pavimento
Wall, ceiling, floor mounting
-  WIPS - Water Infiltration Protection System
-  Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in parallelo 24Vdc
Connect in parallel at 24Vdc
-  Alimentazione integrata, collegare alla tensione di rete 220-240Vac
Built-in driver, connect directly to the line voltage to 220-240Vac
-  530 gr
-  Altamente riciclabile
Highly recyclable






TRIUM P IP67

24Vdc














	7W 24Vdc	15W 24Vdc	Finiture Finish	Colore LED LED Colour	Filtri ottici Optical filters	Elementi di fissaggio Fixing element
Lumen Output 3000K	600lm	1000lm				
 10° Lens	734558. _ _ _ _	734572. _ _ _ _	 4 Nero - Black	 2200K  2700K  3000K  3000K CRI > 90  3500K  4000K	W Senza Filtro Without Filter D Frangiluce Louver F Frangiluce Asy Asy Louver	T Placca di fissaggio Fixing plate V Staffa orientabile H30 Adjustable bracket H30 Z Staffa orientabile H50 Adjustable bracket H50 X Staffa orientabile H80 Adjustable bracket H80
 25° Lens	7G4558. _ _ _ _	7G4572. _ _ _ _				
 40° Lens	744558. _ _ _ _	744572. _ _ _ _				
 60° Lens	754558. _ _ _ _	754572. _ _ _ _				
 Lente ellittica Elliptical lens	774558. _ _ _ _	774572. _ _ _ _				
 Wall Washer	7W4558. _ _ W _					

[1] 2200K
Disponibile solo per la
versione 7W
Available on the 7W
power version only





TRIUM P IP67

220-240Vac

	8W 220-240Vac	Finiture Finish	Colore LED LED Colour	Filtri ottici Optical filters	Elementi di fissaggio Fixing element
Lumen Output 3000K	600lm				
 10° Lens	734582. _ _ _ _	 4 Nero - Black	 2200K  2700K  3000K  3000K CRI > 90  3500K  4000K	W Senza Filtro Without Filter D Frangiluce Louver F Frangiluce Asy Asy Louver	T Placca di fissaggio Fixing plate V Staffa orientabile H30 Adjustable bracket H30 Z Staffa orientabile H50 Adjustable bracket H50 X Staffa orientabile H80 Adjustable bracket H80
 25° Lens	7G4582. _ _ _ _				
 40° Lens	744582. _ _ _ _				
 60° Lens	754582. _ _ _ _				
 Lente ellittica Elliptical lens	774582. _ _ _ _				
 Wall Washer	7W4582. _ _ W _				

[1] 2200K
Disponibile solo per la
versione 7W
Available on the 7W
power version only



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

24Vdc CV20-F-24-N

ACCESSORI
ACCESSORIES

24Vdc



Micro connettore stagno
Micro watertight connector
A00357.40

220-240Vac



Connettore stagno
Watertight connector
A01023.40

EXAMPLE CODE COMPOSITION

