



## CERTIFICATE OF PRODUCT CERTIFICATION

Certificate Number: **012-0108**

***This is to certify that 'Ariel IP67 Standard & Ariel IP67 Plug & Play'  
Model Ref: (see family variants table on page 2)***

Placed on the market by:

# DGA

DGA S.p.A

Via Pietro Nenni 72/B

50013 Z.I. Capalle

Campi Bisenzio (FI)

Italy

***meet the requirements of the LIA/CIBSE Assured Product Verification Scheme  
'TSD-012, v1'***

**15 November 2024**

Date of Initial Registration

**11 April 2025**

Date of Last Issue

**11 April 2028**

Date of Expiry

The validity of this certificate is subject to continuing conformity with The LIA/CIBSE's TSD-012 scheme requirements. The absence of any products listed on certificate but not on the LIA Laboratory certification website indicates that certification of that product is no longer valid.



Kieran Merrills  
Certification Manager

*Signed on behalf of LIA Laboratory Ltd*

Issued by: LIA Laboratory Ltd, Stafford Park 7,  
Telford, Shropshire, TF3 3BQ

For verification of this certificate please visit  
[www.lialabcert.org.uk/certificates-search](http://www.lialabcert.org.uk/certificates-search)

## MANUFACTURER

DGA S.p.A  
Via Pietro Nenni 72/B  
50013 Z.I. Capalle  
Campi Bisenzio (FI)  
Italy

## STANDARD(S)

TM66: 2021  
CEAM Beta

## SCORE(s)

012-0108A (Ariel IP67 standard) 2.6  
012-0108B (Ariel IP67 Plug & Play) 2.7

Delivered by



## FAMILY VARIANT TABLE / PRODUCT CODE EXPLANATION

Product description	Ratings	Power (W)	Fixing system	Dimensions (mm)			Weight (kg)
				L	W	H	
Ariel i IP67	Ta:40°C, IP67	9W LED module (@500mA) & 9.5W LED module (@24Vdc)	Recessed box	-	63Ø	113	0.400
Ariel i IP67 Solovetro					59Ø	116	0.420
Ariel P IP67	Ta:40°C, IP67	9-13W LED module (@500-700mA) & 10-13W LED module (@24Vdc)	Applique, side exit cable, stake, tree strap mounting, stake h350, bollard h350		49Ø	114	0.400
Saturno i IP67	Ta:40°C, IP67	12W LED module (350mA) & 14W LED module @24Vdc	Recessed box		85Ø	127	0.720
Saturno i IP67 Solovetro					80Ø	131	0.770
Saturno P IP67	Ta:40°C, IP67	12-18W LED module (@350-500mA) & 12-18W LED module (@24Vdc)	Applique, side exit cable, stake, tree strap mounting, stake h350, bollard h350		62Ø	140	0.730

Ariel i IP67 P&P	Ta:40°C, IP67	9W LED module (@500mA) & 9.5W LED module (@24Vdc)	Recessed box	-	63Ø	113	0.400
Ariel i IP67 Solovetro P&P					59Ø	116	0.420
Ariel P IP67 P&P		9-13W LED module (@500-700mA) & 10-13W LED module (@24Vdc)	Applique, side exit cable, stake, tree strap mounting, stake h350, bollard h350		49Ø	114	0.400
Saturno i IP67 P&P	Ta:40°C, IP67	12W LED module (@350mA & 14W LED module (@24Vdc)	Recessed box		85Ø	127	0.720
Saturno i IP67 Solovetro P&P					80Ø	131	0.770
Saturno P IP67 P&P	Ta:40°C, IP67	12-18W LED module (@350-500mA) & 12-18W LED module (@24Vdc)	Applique, side exit cable, stake, tree strap mounting, stake h350, bollard h350		62Ø	140	0.730