

MIRUM mR+

IP40 / IP55

Class III

Incasso a parete, soffitto
Wall, ceiling recessed

Collegare in serie 180mA o 250mA o 350mA
Connect in series at 180mA or 250mA or 350mA

315 gr

Ø 78 mm

Altamente riciclabile
Highly recyclable




Alte performance
Massima flessibilità
Ampia scelta di ottiche

High performance
Maximum flexibility
Wide choice of optics


MIRUM mR+ IP40

	6W 180mA	8W 250mA	12W 350mA	12W 350mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	500lm	650lm	900lm	1000lm (at source)		
15° Reflector	7A4250._.	7A4251._.	7A4252._.		<input type="checkbox"/> 7 Bianco - White <input type="checkbox"/> H Nero - Black	<input type="checkbox"/> Y 2700K <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> 9 4000K <input type="checkbox"/> T 3000K CRI > 90 DIM-TO-WARM
25° Reflector	7G4250._.	7G4251._.	7G4252._.			
40° Reflector	744250._.	744251._.	744252._.	744253._T		



MIRUM mR+ IP55

	6W 180mA	8W 250mA	12W 350mA	12W 350mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	500lm	650lm	900lm	1000lm (at source)		
15° Reflector	7A4286._.	7A4287._.	7A4288._.		<input type="checkbox"/> 7 Bianco - White <input type="checkbox"/> H Nero - Black	<input type="checkbox"/> Y 2700K <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> 9 4000K <input type="checkbox"/> T 3000K CRI > 90 DIM-TO-WARM
25° Reflector	7G4286._.	7G4287._.	7G4288._.			
40° Reflector	744286._.	744287._.	744288._.	744289._T		



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

180mA	CC20-F-180-N
250mA	CC9-F-250-N
350mA	CC20-F-350-N
350mA	CC20-A-350-N

ACCESSORI
ACCESSORIES



Filtro Ellittico Linear Filter A00366.80	Nido D'ape Hex Louver A00367.40	Filtro Prismatico Prismatic Filter A00368.80	Filtro Correttivo Softening Lens A00369.80
--	---------------------------------------	--	--

Only for 15° reflector

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH