

NESIS IP67 SOLOVETRO












-  IP67
-  Class III
-  Incasso a parete, pavimento
Wall, floor recessed
-  WIPS - Water Infiltration Protection System
-  Carrabile 2000 kg
Drive over up to 2000 kg
-  Installazione con controcassa obbligatoria
Mandatory installation with recessed box
-  Cavo in neoprene 100 cm
100 cm neoprene cable
(disponibile lunghezza cavo su misura)
(additional cable length available upon request)
-  Collegare in serie 350mA o 500mA
Connect in series at 350mA or 500mA
-  400 gr
-  Altamente riciclabile
Highly recyclable




Versione RGB
Tre finiture disponibili
Alta efficienza

RGB version
Three finishes available
High efficiency

■ NESIS IP67 SOLOVETRO

	3W 350mA	3W RGB 350mA	6W 500mA	Finiture Finish	Colore LED LED Colour
Lumen 3000K	300lm	300lm	450lm		
 10° Lens	733544._ _	733544._7	733545._ _	 3 Grigio - Gray	 U 2200K
 30° Lens	763544._ _	763544._7	763545._ _	 4 Nero - Black	 Y 2700K
 60° Lens	753544._ _	753544._7	753545._ _	 Z Champagne Gold	 6 3000K
					 9 4000K
					 7 RGB <small>Available on some products only</small>




ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

350mA CC20-F-350-N
500mA CC20-F-500-N
350mA RGB CC36-X-350-N

ACCESSORI
ACCESSORIES



Controcassa in alluminio con bordo
Recessed box in aluminum with edge
A00433._0



FINISH
Ø 85 mm



Controcassa materiale plastico con tappo
Recessed box in plastic with closure cap
A00483.40



Connettore stagno
Water-tight connector
A00387.40

EXAMPLE CODE COMPOSITION
123456.

LED COLOUR
FINISH