













## ODINO 6 P

-  IP67
-  Class I
-  Montaggio a parete, soffitto, pavimento  
Wall, ceiling, floor mounting
-  WIPS - Water Infiltration Protection System
-  Cavo in neoprene 200 cm  
200 cm neoprene cable  
(disponibile lunghezza cavo su misura)  
(additional cable length available upon request)
-  DRIVERLESS technology    Collegare alla tensione di rete 220-240Vac  
Connect directly to the line voltage to 220-240Vac
-  350 gr
-  Altamente riciclabile  
Highly recyclable



### ■ ODINO 6 P

	6W 220-240Vac	Finiture Finish	Colore LED LED Colour
Lumen 3000K	450lm		
 30° Lens	763737._ _	<ul style="list-style-type: none"> <li> 3 Grigio - Gray</li> <li> 4 Nero - Black</li> <li> B Bronzo Scuro - Dark Bronze</li> </ul>	<ul style="list-style-type: none"> <li> Y 2700K</li> <li> 6 3000K</li> </ul>
 50° Reflector	7D3737._ _		



#### ACCESSORI ACCESSORIES



Visiera antiabbagliamento  
Low glare visor  
A00519.\_0



Connettore stagno  
Watertight connector  
A01023.40



Picchetto Inox AISI 316L  
Stainless Steel 316L stake  
A00281.60

EXAMPLE CODE COMPOSITION  
123456.

