






TONO B 24V

-  IP40
-  Class III
-  Binario a parete, soffitto
Wall, ceiling mounting track
-  Collegare a binario a bassa tensione 24Vdc
Connect to 24Vdc low voltage track
-  200 gr
-  Altamente riciclabile
Highly recyclable







■ TONO B 24V

	3W 24Vdc	6W 24Vdc	9W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
 3° Lens	7T3754._ _			<input type="checkbox"/> 7 Bianco - White	<input type="checkbox"/> Y 2700K
 10° Lens		733755._ _	733756._ _	<input type="checkbox"/> B Bronzo Scuro Dark Bronze	<input type="checkbox"/> 6 3000K
 30° Lens		763755._ _	763756._ _	<input type="checkbox"/> H Nero - Black	<input type="checkbox"/> W 3000K CRI > 90
 50° Lens		7D3755._ _	7D3756._ _		<input type="checkbox"/> 9 4000K
					<input type="checkbox"/> 1 5000K



■ TONO B 24V

CON NIDO D'APE - WITH HEX LOUVER

	3W 24Vdc	6W 24Vdc	9W 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
 3° Lens	7T3757._ _			<input type="checkbox"/> 7 Bianco - White	<input type="checkbox"/> Y 2700K
 10° Lens		733758._ _	733759._ _	<input type="checkbox"/> B Bronzo Scuro Dark Bronze	<input type="checkbox"/> 6 3000K
 30° Lens		763758._ _	763759._ _	<input type="checkbox"/> H Nero - Black	<input type="checkbox"/> W 3000K CRI > 90
 50° Lens		7D3758._ _	7D3759._ _		<input type="checkbox"/> 9 4000K
					<input type="checkbox"/> 1 5000K

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

24Vdc CV70-F-24-N



Binari 24Vdc e accessori
24Vdc tracks and accessories

EXAMPLE CODE COMPOSITION
123456.

