

## TONO P

IP40

Class III

Montaggio a parete, soffitto, pavimento  
Wall, ceiling, floor mounting

Collegare in serie 500mA o 700mA o 900mA  
Connect in series at 500mA or 700mA or 900mA

180 gr

Altamente riciclabile  
Highly recyclable




**Luce puntuale**  
**Sorgente piccola e compatta**  
**Cablaggio semplificato**

Spot light  
Small and compact source  
Simplified wiring

### TONO P

	3W 900mA	6W 500mA	9W 700mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
3° Lens	7T4402._ _			3 Grigio - Gray	Y 2700K
10° Lens	734403._ _ 734404._ _			4 Nero - Black	6 3000K
30° Lens	764403._ _ 764404._ _			T Titanio - Titanium	W 3000K CRI > 90
50° Lens	7D4403._ _ 7D4404._ _			Z Champagne Gold	J 3500K
					9 4000K



NOTA:  
È possibile richiedere  
versione da incasso con molle

Recessed version with springs  
available upon request

### TONO P

CON NIDO D'APE - WITH HEX LOUVER

	3W 900mA	6W 500mA	9W 700mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	250lm	500lm	650lm		
3° Lens	7T4405._ _			3 Grigio - Gray	Y 2700K
10° Lens	734406._ _ 734407._ _			4 Nero - Black	6 3000K
30° Lens	764406._ _ 764407._ _			T Titanio - Titanium	W 3000K CRI > 90
50° Lens	7D4406._ _ 7D4407._ _			Z Champagne Gold	J 3500K
					9 4000K

ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

500mA	CC20-F-500-N
700mA	CC20-F-700-N
900mA	CC20-F-900-N

EXAMPLE CODE COMPOSITION  
123456.

