

TRATTO



IP40



Class III



Montaggio a parete, soffitto, pavimento
Wall, ceiling, floor mounting



Collegare in parallelo 24Vdc
Connect in parallel at 24Vdc



90 gr/m




Altamente riciclabile
Highly recyclable




TRATTO

	8W/m 24Vdc	12W/m 24Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K Opal cover Transparent cover	400lm/m 700lm/m	600lm/m 1000lm/m		
Senza fissaggio Without fixing			<ul style="list-style-type: none"> 3 Grigio - Gray 4 Nero - Black 	<ul style="list-style-type: none"> U 2200K Q 2500K X 2700K CRI > 90 W 3000K CRI > 90 K 3500K CRI > 90 D 4000K CRI > 90
Copertura opalina Opal cover	OFP1- _ _ _ _ _	O3FP1- _ _ _ _ _		
Copertura trasparente Transparent cover	OF21- _ _ _ _ _	O3F21- _ _ _ _ _		
Fissaggio con magneti Magnets fixing				
Copertura opalina Opal cover	O6FP1- _ _ _ _ _	O7FP1- _ _ _ _ _		
Copertura trasparente Transparent cover	O6F21- _ _ _ _ _	O7F21- _ _ _ _ _		
Fissaggio con biadesivo Double sided tape fixing				
Copertura opalina Opal cover	O1FP1- _ _ _ _ _	O4FP1- _ _ _ _ _		
Copertura trasparente Transparent cover	O1F21- _ _ _ _ _	O4F21- _ _ _ _ _		



Lunghezze ottimizzate (cm) Optimized lengths (cm)

007	012	018	023	029	034	040	045	051	056	062	067	073	078	084	089	095	100	106	111	117	122	128	133	139	144
150	155	161	166	172	177	183	188	194	199	205	210	216	221	227	232	238	243	249	254	260	265	271	276	282	287
293	298																								



Misure personalizzate su richiesta Custom lengths upon request

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)


24Vdc CV70-F-24-N

ELEMENTI DI FISSAGGIO
FIXING ELEMENTS


Specifiche tecniche
Technical data




Staffa con vite
Bracket with screw
A00529_ 0




Staffa con vite 45°
Bracket with screw 45°
A00845_ 0



Staffa magnetica
Magnetic bracket
A00534_ 0



Staffa magnetica 45°
Magnetic bracket
A00844_ 0



Clip di fissaggio a molla
Mounting clip
A00706_ 0