












AURORA 3000 PL AURORA 4000 PL

-  IP40
-  Class III
-  Montaggio a parete, soffitto, pavimento
Wall, ceiling, floor mounting
-  Collegare in serie 600mA o 700mA o 900mA
Connect in series at 600mA or 700mA or 900mA
-  750 gr
-  Altamente riciclabile
Highly recyclable






AURORA 3000 PL

	25W 700mA	20W 600mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	3000lm	1750lm at source		
 10° Reflector	733904._ _		<input type="checkbox"/> 7 Bianco - White <input type="checkbox"/> H Nero - Black <input type="checkbox"/> W All White	<input type="checkbox"/> Y 2700K <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> 9 4000K <input type="checkbox"/> T 3000K CRI > 90 DIM-TO-WARM
 20° Reflector	783904._ _			
 30° Reflector	763904._ _			
 40° Reflector	743904._ _	743967._ T DIM-TO-WARM		



AURORA 4000 PL

	30W 900mA	25W 700mA	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	4000lm	2000lm at source		
 20° Reflector	784254._ _		<input type="checkbox"/> 7 Bianco - White <input type="checkbox"/> H Nero - Black <input type="checkbox"/> W All White	<input type="checkbox"/> Y 2700K <input type="checkbox"/> 6 3000K <input type="checkbox"/> W 3000K CRI > 90 <input type="checkbox"/> 9 4000K <input type="checkbox"/> T 3000K CRI > 90 DIM-TO-WARM
 30° Reflector	764254._ _			
 40° Reflector	744254._ _	744258._ T DIM-TO-WARM		

ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

600mA	CC36-A-600-N
700mA	CC50-F-700-N
700mA	CC36-A-700-N
900mA	CC50-F-900-N

DIM-TO-WARM

ACCESSORI
ACCESSORIES



Nido D'ape
Hex Louver
A00959.40

EXAMPLE CODE COMPOSITION
123456.

