









## MINI TINI B 48V DOUBLE

-  IP40
-  Class III
-  Binario a parete, soffitto  
Wall, ceiling mounting track
-  Collegare a binario a bassa tensione 48Vdc  
Connect to 48Vdc low voltage track
-  52 gr
-  Altamente riciclabile  
Highly recyclable



### MINI TINI B 48V DOUBLE


	1W x 2 48Vdc	2W x 2 48Vdc	Finiture Finish	Colore LED LED Colour
Lumen 3000K	2 x 100lm	2 x 150lm		
 10° Lens	734186._ _	734187._ _	<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: black; margin-right: 5px;"></span> 4 Nero - Black</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: white; border: 1px solid black; margin-right: 5px;"></span> 7 Bianco - White</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #8B4513; margin-right: 5px;"></span> B Bronzo Scuro Dark Bronze</li> </ul>	<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #FFD700; margin-right: 5px;"></span> U 2200K</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #FFD700; border: 1px solid black; margin-right: 5px;"></span> X 2700K CRI &gt; 90</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #FFD700; border: 1px solid black; margin-right: 5px;"></span> W 3000K CRI &gt; 90</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #FFD700; border: 1px solid black; margin-right: 5px;"></span> 9 4000K</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #FFD700; border: 1px solid black; margin-right: 5px;"></span> 1 5000K</li> </ul>
 25° Lens	7G4186._ _	7G4187._ _		
 40° Lens	744186._ _	744187._ _		
 60° Lens	754186._ _	754187._ _		



### MINI TINI B 48V DOUBLE

CON VISIERA - WITH VISOR

	1W x 2 48Vdc	2W x 2 48Vdc	Finiture Finish	Colore LED LED Colour
Lumen 3000K	2 x 100lm	2 x 150lm		
 10° Lens	734236._ _	734237._ _	<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: black; margin-right: 5px;"></span> 4 Nero - Black</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: white; border: 1px solid black; margin-right: 5px;"></span> 7 Bianco - White</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #8B4513; margin-right: 5px;"></span> B Bronzo Scuro Dark Bronze</li> </ul>	<ul style="list-style-type: none"> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #FFD700; margin-right: 5px;"></span> U 2200K</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #FFD700; border: 1px solid black; margin-right: 5px;"></span> X 2700K CRI &gt; 90</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #FFD700; border: 1px solid black; margin-right: 5px;"></span> W 3000K CRI &gt; 90</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #FFD700; border: 1px solid black; margin-right: 5px;"></span> 9 4000K</li> <li><span style="display: inline-block; width: 10px; height: 10px; background-color: #FFD700; border: 1px solid black; margin-right: 5px;"></span> 1 5000K</li> </ul>
 25° Lens	7G4236._ _	7G4237._ _		
 40° Lens	744236._ _	744237._ _		
 60° Lens	754236._ _	754237._ _		



ALIMENTATORI CONSIGLIATI (non inclusi)  
SUGGESTED DRIVERS (not included)

48Vdc CV70-F-48-N



Micro Binari 48Vdc  
48Vdc Micro Track

\* Prevedere 1 indirizzo DALI  
per ogni Mini Tini B 48V Double  
Please consider 1 DALI address  
for each Mini Tini B 48V Double

EXAMPLE CODE COMPOSITION  
123456.

