

TINI B 48V

IP40

Class III

Binario a parete, soffitto
Wall, ceiling mounting track

Collegare a binario a bassa tensione 48Vdc
Connect to 48Vdc low voltage track


90 gr

Altamente riciclabile
Highly recyclable




TINI B 48V

	3W 48Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	300lm		
15° Lens	7A4182._ _	7 Bianco - White	U 2200K
30° Lens	764182._ _	B Bronzo Scuro Dark Bronze	X 2700K CRI > 90
60° Lens	754182._ _	H Nero - Black	W 3000K CRI > 90
Lente ellittica Elliptical lens	774182._ _		9 4000K
			1 5000K



TINI B 48V DOUBLE

	3W x 2 48Vdc	Finiture Finish	Colore LED LED Colour
Lumen Output 3000K	2 x 300lm		
15° Lens	7A4185._ _	7 Bianco - White	U 2200K
30° Lens	764185._ _	B Bronzo Scuro Dark Bronze	X 2700K CRI > 90
60° Lens	754185._ _	H Nero - Black	W 3000K CRI > 90
Lente ellittica Elliptical lens	774185._ _		9 4000K
			1 5000K



ALIMENTATORI CONSIGLIATI (non inclusi)
SUGGESTED DRIVERS (not included)

48Vdc CV70-F-48-N



Micro Binari 48Vdc
48Vdc Micro Track

* Prevedere 1 indirizzo DALI
per ogni Tini B 48V / Tini B 48V Double
Please consider 1 DALI address
for each Tini B 48V / Tini B 48V Double

EXAMPLE CODE COMPOSITION
123456.

